

107 0771

Continental Oil Co.		St. Louis Rocky Mt.		16-29N-22E	
Company	Well No.	Lease	& Pac. Co. S-T-R		
Location	1930' fr. N. L. 660'	fr. H. L.	County Colfax		
Spud	2-21-55	Comp.	3-21-55	Field Wildcat	
Total Depth	2890' sd.	P. B.	Top Pay	Size	CSG. RECORD
I. P.		per day	10 3/4	230	Sax 175
Ch.	on	Tbg. @	Press: T.		
C.	Pkr.	Gor.	Gr.		
PLUGGED AND ABANDONED.					
DST 2668-2709 op 2 hrs, rec 120' mud & 360'			S/S FORMATION RECORD		
(c fresh wtr, FP 290%, 30min SIP 880%)			Elev. 6464' Gr.		
DST 2700-2720 straddle pkr test, op 2 hrs,			T Timpas	T	2200
rec 240' wtr c mud, FP 120%, 30 min SIP			T Carlyle	T	2283
930%			T Greenhorn	T	2384
DST 2615-2640 straddle pkr test, op 2 hrs,			T Graneros	T	2450
Treatments: rec 2000' wtr c mud, pkr failed, no			T Dakota	T	2610
press. recorded.			T Morrison	T	2787
C-105 Rpts: NW SW; Rotary tools: 0-TD; Drlg.			T	T	
Cont. Carmack Drlg. Co., Mile High Center,			T	TGr.	
Denver, CO.					

COLFAX COUNTY	NEW MEXICO	16-29N-22E
Well:	Result:	
Locn: CONTINENTAL OIL CO. #5 St. Louis, Rocky Mountain & Pacific Railway Company	D&A	
16-29N-22E, SW NW; N/cent part cty, wildcat 12 mi SW Raton; Raton Basin test 7/8 mi NE of the #4 St. Louis, 4709' dry hole which logged SO in Dakota sand at 2795-2842'		
Spud: 2-21-55 Comp: 3-21-55 Elev: 6473' DF TD: 2882'		
Casing: 10 3/4" 230'/175sx		
Prod Zone: None		
Comp Info: Crd 2679-2709', rec 27' being 5' blk sh, 6' dk gray med-grnd sd w/spotted fluor & odor, 7' gray med-grnd sd w/spotty fluor & stn, 5' gray hard sd w/NS, 1' med-grnd sd w/good por, fluor, stn & gas odor, 2' f-grnd tite sd w/fluor & stn; DST 2668-2709', op 2 hrs, rec 120' mud & 360' GC frsh wtr, FP 290%, SIP 880%/30 min; Crd 2709-80', rec 41' being 8' gray med-grnd tite sd w/fluor, stn & gas odor, 5' blk sh, 28' white f-grnd sd w/fair por & sat w/wtr; Crd 2750-91', rec 41' being 30' white sd w/NS, 7' hard gray sd w/NS, 4' grn hard sh; DST 2700-2720', op 2 hrs, rec 240' SWCM, FP 120%, SIP 930%/30 min; Crd 2791-2823', rec 32' grn sh & siltstone; DST 2650-88' (straddle pkr), op 2 hrs, rec 20' mud, FP 0, SIP 0/		
<i>L. R. R. R.</i> OIL REPORTS: Date: 4-1-55 Card No: 1 NM 1m		

COLFAX COUNTY	NEW MEXICO	16-29N-22E
Well:	Result:	
Locn: CONTINENTAL OIL CO. #5 St. Louis, Rocky Mountain & Pacific Railway Company, continued		
16-29N-22E, SW NW; N/cent part cty, wildcat 12 mi SW Raton; Raton Basin test 7/8 mi NE of the #4 St. Louis, 4709' dry hole which logged SO in Dakota sand at 2795-2842'		
Spud: 2-21-55 Comp: 3-21-55 Elev: 6473' DF TD: 2882'		
Casing: 10 3/4" 230'/175sx		
Prod Zone: None		
Comp Info: Crd 2679-2709', rec 27' being 5' blk sh, 6' dk gray med-grnd sd w/spotted fluor & odor, 7' gray med-grnd sd w/spotty fluor & stn, 5' gray hard sd w/NS, 1' med-grnd sd w/good por, fluor, stn & gas odor, 2' f-grnd tite sd w/fluor & stn; DST 2668-2709', op 2 hrs, rec 120' mud & 360' GC frsh wtr, FP 290%, SIP 880%/30 min; Crd 2709-80', rec 41' being 8' gray med-grnd tite sd w/fluor, stn & gas odor, 5' blk sh, 28' white f-grnd sd w/fair por & sat w/wtr; Crd 2750-91', rec 41' being 30' white sd w/NS, 7' hard gray sd w/NS, 4' grn hard sh; DST 2700-2720', op 2 hrs, rec 240' SWCM, FP 120%, SIP 930%/30 min; Crd 2791-2823', rec 32' grn sh & siltstone; DST 2650-88' (straddle pkr), op 2 hrs, rec 20' mud, FP 0, SIP 0/		
<i>L. R. R. R.</i> OIL REPORTS: Date: 4-1-55 Card No: 1 NM 1m		

16-29N-22E, SW NW; N/cent part cty, wildcat 12 mi SW Raton; Raton Basin test 7/8 mi NE of the #4 St. Louis, 4709' dry hole which logged SO in Dakota sand at 2795-2842'

Spud: 2-21-55 Comp: 3-21-55 Elev: 6473' DF TD: 2882'

Casing: 10 3/4" 230'/175sx

Prod Zone: None

Comp Info: Crd 2679-2709', rec 27' being 5' blk sh, 6' dk gray med-grnd sd w/spotted fluor & odor, 7' gray med-grnd sd w/spotty fluor & stn, 5' gray hard sd w/NS, 1' med-grnd sd w/good por, fluor, stn & gas odor, 2' f-grnd tite sd w/fluor & stn; DST 2668-2709', op 2 hrs, rec 120' mud & 360' GC frsh wtr, FP 290%, SIP 880%/30 min; Crd 2709-80', rec 41' being 8' gray med-grnd tite sd w/fluor, stn & gas odor, 5' blk sh, 28' white f-grnd sd w/fair por & sat w/wtr; Crd 2750-91', rec 41' being 30' white sd w/NS, 7' hard gray sd w/NS, 4' grn hard sh; DST 2700-2720', op 2 hrs, rec 240' SWCM, FP 120%, SIP 930%/30 min; Crd 2791-2823', rec 32' grn sh & siltstone; DST 2650-88' (straddle pkr), op 2 hrs, rec 20' mud, FP 0, SIP 0/

L. R. R. R.

OIL REPORTS: Date: 4-1-55 Card No: 1 NM 1m