

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	NEW MEXICO OIL CONSERVATION COMMISSION RECEIVED JAN 27 1941
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Maxwell, N.M.

January 24th 1941

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the **Tex-Mex no 1**

Golfax Carbon Dioxide Corp. Tex-Mex Cattle Co., Well No. 1 in the
Company or Operator Lease

of Sec. 2, T. 26, R. 24, N. M. P. M.,
Field, Golfax County.

The dates of this work were as follows: November 8th 1940 to January 13, 1941

Notice of intention to do the work was (was not) submitted on Form C-102 on _____ 19____

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Nov. 8, 1940 plugged hole above gas up to 5' below casing, run 16 sacks Ideal Portland cement under water and stem pressure, let set 12 days drilled out cement, did not have complete water shut off under casing. December 5th plugged well 8' above gas and run 2 sacks quick set cement water pressure set 13 days drilled out made test and had complete moisture shut off under casing. Drilled out gas plug and drilled below gas sand about 8 1/2' got small amount of moisture, plugged up with lead wool from bottom of hole to near gas sand about 1515' almost complete water or moisture shut off may be small amount of moisture coming just under gas sand. Now have the well completed with valve on for State inspection. Drilling machine stranding over well.

Witnessed by _____ Name _____ Company _____ Title _____

Subscribed and sworn before me this 6th

I hereby swear or affirm that the information given above is true and correct.

day of Feb., 1941

Name York Denton

Position President

Representing Golfax Carbon Dioxide Corp.
Company or Operator

My commission expires May 18, 1943

Address Maxwell, New Mexico

Remarks:

J. C. Rodgers
Name
Manager
Title

new mexico oil con. comm.
see

