## JIL ZONSERVATION COMM.JSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

	Indicate nature of	Topoli by choosing		
REPORT ON BEGINNING DRILL TIONS	LING OPERA-	REPORT O	N REPAIRING WELL	
REPORT ON RESULT OF SHOOT ICAL TREATMENT OF WEL	ING OR CHEM-		N PULLING OR OTHERWIS RING CASING	E
REPORT ON RESULT OF TEST ( SHUT-OFF	OF CASING	REPORT O	N DEEPENING WELL	
REPORT ON RESULT OF PLUGO	SING OF WELL	x		
	Pampa	, Texas,	April 2, 1945	•
OIL CONSERVATION COMMISS: SANTA FE, NEW MEXICO. Gentlemen:	·	Place	Date	
Following is a report on the work of W. A. KATES & E. C. SID			Well No.	in the
SE SE Company or Operator	of Sec35	Lease 278	, R24E	N. M. P. M.,
Wildet	Field,	Colfax		Country
The dates of this work were as follow	gtartag to	lugging March	24th and completed Mar	
Notice of intention to do the work	was (was not) subm	itted on Form C-102	on March 29,	19 <b>45</b> •
DETAILED Modded back and bridged 18-5/8" casing 61' above 1 in hole: then placed bear	1440 casing po	ork Done And R and dumped 10 s bint, and pulle primately 830	esults obtained acks mixed coment. In the second se	i cement:
DETAILED Mudded back and bridged 18-5/8" casing 61° above 1 in hole; then placed heav ripped 10-3/4" casing abothe hole; placed heavy 122" Casing; we then place	ACCOUNT OF WO nois at 1430° a 1440° casing po my mud to appro- ove the casing mud back to 425 sed heavy mud to	ork DONE AND Rund dumped 10 soint, and pulle mimately 830' point 30' and o' and run 10 so top and run	esults obtained acks mixed cecent. Is d 8-5/8" casing leaving and run 10 sacks mixed pulled 10-3/4" leaving acks mixed cement and	ng 61° i cement; g 30° in pulled
Madded back and bridged 18-5/8" casing 61 above 1 in hole; then placed heav ripped 10-3/4" casing aboth hole; placed heavy 12½" Casing; we then placed 4" x 4" market J. W. Phill	ACCOUNT OF WO nois at 1430° a 1440° casing por y mud to approve the casing mud back to 425 and heavy mud to at mouth of w	ork DONE AND Rund dumped 10 soint, and pulle mimately 830' point 30' and o' and run 10 so top and run	esults obtained acks mixed cessort. Is d 8-5/8" casing leaving and run 10 sacks mixed pulled 10-3/4" leaving acks mixed cement and 5 sacks cement on top	ng 61° i cement; g 30° in pulled
Madded back and bridged 18-5/8" casing 61 above 1 in hole; then placed heav ripped 10-3/4" casing abothe hole; placed heavy 1122" Casing; we then placed 4" x 4" market	ACCOUNT OF WO nois at 1430° a 1440° casing por y mud to approve the casing mud back to 425 and heavy mud to at mouth of w	ork DONE AND Rend dumped 10 a pint, and pulle mimately 830' point 30' and i' and run 10 a to top and run sell.	esults obtained acks mixed cecent. It d 8-5/8" casing leaving and run 10 sacks mixed pulled 10-3/4" leaving acks mixed cement and 5 sacks cement on top	ng 61° i cement; g 30° in pulled of hole
Madded back and bridged 18-5/8" casing 61 above 1 in hole; then placed heav ripped 10-3/4" casing aboth hole; placed heavy 12½" Casing; we then placed 4" x 4" market J. W. Phill	ACCOUNT OF WOLLOW at 1450° at 1450° casing pory mud to approprie the easing mud back to 425 and heavy mud to at mouth of white this	ork DONE AND Rend dumped 10 soint, and pulle mimately \$30 point 30 and run 10 so top and run tell.  Oil Well Server is true and corrections.	esults obtained acks mixed cecent. It d 8-5/8" casing leaving and run 10 sacks mixed pulled 10-3/4" leaving acks mixed cement and 5 sacks cement on top	ng 61' i cement; g 30' in pulled of hole foolpusher.
Madded back and bridged 18-5/8" casing 61 above 1 in hole; then placed heavy ripped 10-3/4" casing about the hole; placed heavy 122" Casing; we then place and placed 4" x 4" market Witnessed by J. W. Phillips Subscribed and sworn before me	ACCOUNT OF WOOD ALLO CASING PORT OF WILL AND CASING PORT OF THE CASING BUT ALL MOUTH OF THE CASING PORT OF T	ork DONE AND Rend dumped 10 soint, and pulle minately 830 point 30 and run 10 so top	esults obtained acks mixed cecent. It d 8-5/8" casing leaving and run 10 sacks mixed pulled 10-3/4" leaving acks mixed cement and 5 sacks cement on top dicing Co.	ng 61' i cement; g 30' in pulled of hole  Coolpusher. Title
Madded back and bridged 18-5/8" casing 61 above 1 in hole; then placed heavy ripped 10-3/4" casing about the hole; placed heavy 122" Casing; we then place and placed 4" x 4" market Witnessed by J. W. Phillips Subscribed and sworn before me	ACCOUNT OF WOLLOW at 1450° at 1450° casing pory mud to approprie the easing mud back to 425 and heavy mud to at mouth of white this	Comp  I hereby swear is true and corresponding to the corresponding to t	esults obtained acks mixed cedent. It d 8-5/8" casing leaving and run 10 sacks mixed pulled 10-3/4" leaving acks mixed cement and 5 sacks cement on top dicing Co.  Transport of affirm that the information company	ng 61' i cement; g 30' in pulled of hole  Coolpusher. Title
Madded back and bridged I 8-5/8" casing 61 above 1 in hole; then placed heavy ripped 10-3/4" casing about the hole; placed heavy 12½" Casing; we then place and placed 4" x 4' market Witnessed by	ACCOUNT OF WO Acie at 1430 a 1440 casing portion the easing mud back to 425 and heavy mud to a mouth of a 1450 and heavy mud to a 1450 and heavy mud t	Companies true and correspond to a companies true and correspond to a corresponding to the co	esults obtained acks mixed cedent. It d 8-5/8" casing leaving and run 10 sacks mixed pulled 10-3/4" leaving acks mixed cement and 5 sacks cement on top dicing Co.  The partner of the par	ng 61' i cement; g 30' in pulled of hole  Coolpusher. Title

ale to the constant of the con

And the state of t