•		
NO. OF COPIES RECEIVED	T	
DISTRIBUTION	 	Form C-103 Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103
FILE	WER MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
U.S.G.S.	 	Sa. Indicate Type of Lease
LAND OFFICE		State Fee X
OPERATOR	† 	5. State Oil & Gas Lease No.
	•	
(DO NOT USE THIS F	SUNDRY NOTICES AND REPORTS ON WELLS ORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. E "APPLICATION FOR PERMIT -" (FORM C-1011 FOR SUCH PROPOSALS.)	
OIL GAS		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
O DESSA NATU	RAL CORPORATION	Odessa Natural Corp.
P. O. Box 39	908, Odessa, Texas 79760	9. Well No.
4. Location of Well M	342 West 537	10. Field and Pool, or Wildcat
UNIT LETTER	FEET FROM THE LINE AND FEET FROM	Wildcat
South	LINE, SECTION 19E TOWNSHIP PARSE NAMES NAMED NAMED	
amminini	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	GR 7271', KB 7284'	Colfax
16.	Check Appropriate Box To Indicate Nature of Notice, Report or Otl	her Data
NOTI	CE	REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JQB X	
OTHER	OTHER	
OTHER		
17. Describe Proposed or Co work) SEE RULE 1103.	empleted Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed
MAY 4, 1972	TD 4847'	
	D 110 14 C TH 02 07 00 140 H 27 17 17 17 17 17 17 17 17 17 17 17 17 17	
	Ran 112 jts. of 7" OD 23.00#/ft. K-55 LT&C Range III @ 4843' KB. Cemented with 150 sacks regular cement w	casing 4831'. Landed /3% CaC12.
	Ran 112 jts. of 7" OD 23.00#/ft. K-55 LT&C Range III @ 4843' KB. Cemented with 150 sacks regular cement w Held 1500 psi - 30 minutes.	casing 4831'. Landed /3% CaCl ₂ .
	@ 4843' KB. Cemented with 150 sacks regular cement w	casing 4831'. Landed /3% CaCl ₂ .
	@ 4843' KB. Cemented with 150 sacks regular cement w Held 1500 psi - 30 minutes.	casing 4831'. Landed /3% CaCl ₂ .
	@ 4843' KB. Cemented with 150 sacks regular cement w Held 1500 psi - 30 minutes.	casing 4831'. Landed /3% CaCl ₂ .
	@ 4843' KB. Cemented with 150 sacks regular cement w Held 1500 psi - 30 minutes. Top of cement by calculation 4100'.	/3% CaCl ₂ .
Distribution:	@ 4843' KB. Cemented with 150 sacks regular cement w Held 1500 psi - 30 minutes. Top of cement by calculation 4100'.	/3% CaCl ₂ .

Manager - Production

me Wil & She Shispector

5/5/72