

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SAN ANTONIO		
FILE		
U.S.C.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator ODESSA NATURAL CORPORATION		5. State Oil & Gas Lease No.
3. Address of Operator P. O. Box 3908, Odessa, Texas 79760		7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>E</u> <u>380</u> FEET FROM THE <u>West</u> LINE AND <u>1829</u> FEET FROM THE <u>North</u> LINE, SECTION <u>30</u> TOWNSHIP <u>30N</u> RANGE <u>20E</u> NMPM.		8. Farm or Lease Name <u>ODESSA NATURAL CORP. - MAGUIRE OIL CO. W S RANCH</u>
15. Elevation (Show whether DF, RT, GR, etc.) GR 7079' KB 7089'		9. Well No. 2
		10. Field and Pool, or Wildcat Wildcat
		12. County Colfax

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

February 14, 1973 TD 4887'

Ran 114 joints of 7" OD 23.0#/ft. K-55 ST&C Range III used casing 4877'. Landed @ 4887' KB. Cemented with 50 sacks regular cement w/3% CaCl₂ and 100 sacks Class H with 3% HA-5.

Held 800# - 30 minutes.

Calculated top of cement @ 4460'.

3/NMOCC-Santa Fe, 2/Maguire, 1/WSRanch, 1/CM, 1/RLH, 1/JH, 1/JJS, 1/WFile

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>John J. Strojek</u> John J. Strojek/so	TITLE <u>Manager - Production Dept.</u>	DATE <u>2/16/73</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>[Signature]</u>	DATE <u>2/15/73</u>
CONDITIONS OF APPROVAL, IF ANY:		