

Contractor Coffey Drilling Co.
 Rig No. 1
 Spot 660' FSL-660' FWL
 Sec. 27
 Twp. 31 N
 Rng. 25 E
 Field Wildcat
 County Colfax
 State New Mexico
 Elevation 8341' "Ground"
 Formation "Dakota" Sand

Top Choke 3/4"
 Bottom Choke 9/16"
 Size Hole 6 3/4"
 Size Rat Hole None
 Size & Wt. D. P. 2 7/8" 10.40
 Size Wt. Pipe None
 I. D. of D. C. 2 1/8"
 Length of D. C. 280'
 Total Depth 3405'
 Interval Tested 3331-3405
 Type of Test Straight

Tool Open @ 4:45 P M.

Flow #1 5 Min. SIP #1 45 Min. Flow #2 45 Min. SIP #2 45 Min.

Flow #3 Min. SIP #3 Min. Flow #4 Min. SIP #4 Min.

B. H. T. 118°

Mud Wt. 9.5

Gravity

Viscosity 47

TOOL SEQUENCE

3323-----

3331-----

TD 3405-----

PRD Make Kuster AK-1

No. 1106 Cap. 4500 @ 3312
 Press Field Corrected

IH	A	1636	1636
FH	K	1629	1629
Flow #1-IF	B	5	9
FF	C	7	17
SIP #1	D	210	204
Flow #2-IF	E	12	20
FF	F	42	54
SIP #2	G	197	202
Flow #3-IF	H	None	Taken
FF	I	"	"
SIP #3	J	"	"

Pressure Below
Bottom Packer
Bled To

Our Tester: Don Margheim

Witnessed By: John Cranor

RECOVERY IN PIPE

DID WELL FLOW - Gas No Oil No Water No

70' Drilling mud = .31 Bbl. - No show of oil or gas.

REMARKS:

1st Flow - Tool opened with a weak blow, decreasing to near dead at end of period.

2nd Flow - Tool opened with a puff blow, dead immediately. By-passed tool (point "X" on chart) after open 30 minutes, had a weak blow, dead in 30 seconds. Dead to end of test.

Corrected pressures in 1/2 minute increment readings on following page.

ADDRESS

410 Denver Center Bldg., Denver, Colo.

Date 12-23-72

Inv. 11111 copies

T-15726

R-1106

