STATE OF NEW ME	XICO
ENERGY AND MILIERALS DE	PARTMEN
. ** *** ******	
DISTRUCTION	

OIL CONSERVATION DIVISION

DISTRIBUTION	P. O. BOX 2088	
ANTA FE	SANTA FE, NEW MEXICO 87	5 (
1) 7		

SANTAFE	SANTA FE, NEV	V MEXICO 87501	A - 1 (80 <u>1 - 1</u>		
FILE			la ladicate	Type of Leuse	
U.S.O.S.		Control Control	State Oil (Г•• []	
LAND OFFICE			S Signe Oil 6	Gos Leose No.	
DPERATOR			7		
SUNDRY N	OTICES AND REPORTS ON	WELLS			
1. OIL CAB WELL C	THER. X Dry Hole		7, Unit Agree		
2. Name of Operator			8. Famor Le	lase Name	
Bennett Petroleum Co	rnoration		Phelps	Phelps-Dodge	
1. Address of Operator	poración		9. Well No.	<u> </u>	
Suite 630, 1580 Lincoln St., Denver, Colo. 80203				3-Y	
4. Location of Well			l Wildes	Wildcat	
THE West LINE, SECTION	5 PEET PROM THE South 9 TOWNSHIP 28		///////		
mmmmmm	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County		
6573' GR, 6586' KB			Colfax		
16. Check Appr	opriate Box To Indicate N	lature of Notice, Report of	or Other Data		
NOTICE OF INTEN	-		UENT REPORT C	F:	
PERFORM REMEDIAL WORK	PLUE AND ABANDON	COMMENCE DRILLING DPNS. CASING TEST AND CEMENT JQS	- ب	TERING CASING	
97HER	ons (Clearly state all pertinent desc	other	luding estimated date	of starting any propo	
work) SEE RULE 1103.					
On March 5, 1981, mor	ved-in and rigged-	up wireline unit a	and mast tru	ick. On	

On March 3, 1901, moved-in and rigged-up wireline unit and mast truck. On March 6, 1981, ran 6.40" gauge ring and junk basket to 2006', could go no further. Ran 1-11/16" CCL tools to 2049', could go no further. Ran CCL log, 2049' to 1790'. Set CIBP ± 1910'. Using dump bailer, capped CIBP with a 6' cement plug. Rigged down wireline equipment. Installed a 7" x 2" swage and a 2" 2000 psi WP valve.

		·
18. I hereby certify that the information above in true and com	polare to the best of my knowledge and belief.	
Neate R. F. Ronnett		3/16/81
Carl Ulvog	TIPLE SENIOR PETROPED . DID COIST	3/25/81