THE ST AND MINERALS DE	OIL CONSERVATION DIVISION	
DISTRIBUTION	P. O. BOX 2088	Form C-103
SANTA FE	SANTA FE, NEW MEXICO 87501	Revised 10-1-78
PILE .		5a. Indicate Type of Lease
LAND OFFICE		State Fee X
OPENATOR		5. State Otl & Gas Lease No.
	Programme Services	
	SUNDRY NOTICES AND REPORTS ON WELLS	
TO PER 380 TON OOT	M FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1.		7. Unit Agreement Name
well well	CARBON DIOXIDE	
2. Name of Operator		8. Farm or Lease Name
HNG FOSSIL FUE	LS COMPANY	T. L. ROACH
· ·	EET, SUITE 1505 Americana Bldg., Houston, Texas 77002	3. Well No.
4. Location of Well	mir, seria 1909 racricula blug., nouscon, rexas //002	10. Field and Pool, or Wildcat
Н	1980 rest from the North Line and 660 rest from	
UNIT LETTER	FEET FROM THE LINE AND FEET FROM	WILDCAT
East	NE, SECTION 1 TOWNSHIP 29N RANGE 25E NMPM.	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
ÖMMA	GR = 6660'	COLFAX
10.	Check Appropriate Box To Indicate Nature of Notice, Report or Otl	ner Data
NOTIC	E OF INTENTION TO: SUBSEQUENT	REPORT OF:
	\text{\tin}\text{\tex{\tex	
PERFORM REMEDIAL WORK	PLUG AND ABANDON X REMEDIAL WORK	ALTERING CASING
TEMPORARILY ASANDON PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	PLUG AND ASANDONMENT
	OTHER	П
GTHER		
		
work) SEE RULE 1103.	pleted Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed
		•
June 29, 1979	Set at 348' - 9-5/8" O.D., 32.30#, H-40, S.T. & C.,	R-3 surface casing
	cemented with 200 sxs cement - circulated.	1 3 surface casing -
7]]]]000		
July 11, 1979	Set at 2160' - 7" O.D., 20.00#, K-55, S.T. & C., R-3	, production casing -
••	cemented with 75 sxs cement. Tagged top of cement a	t 2132'.
July 20, 1979	TD = 3797! = spotted 42 syr sement plant from 27071	05051
20, 23,3	TD - 3797' - spotted 43 sx. cement plug from 3797' t sx cement plug from 3450' to 3350'. Spotted 85 sx c	o 3597'. Spotted 21
	to 2100' PBTD - 2100' - Well temp. Aband July	ement plug from 2500'
	Herr carp. Abana bary	21, 19/9.
PROPOSED:	Set a 20 sx. (100') cement plug in the top of the 7"	O.D. casing from 100! +
	surface.	o.s. casing name io
•	"Well will be filled with 10# fresh water mud betwee	n plugs."
	Set a steel marker of at least 4" in diameter, set i	n concrete, and extending
	at least four feet above mean ground level. The name	e and number of the wall
•	and its location (Unit Letter, Section, Township, an	d Range) permanently
	engraved into the metal of the marker.	
18 I hanshu anaklin shina shini 1 a	prmation above is true and complete to the best of my knowledge and belief.	
to a revery certify that the thic	American shows in true and complete to the best of my unowiedge and belief.	
Michael &	PRODUCTION ANALYST	Octobron as asset
Ollaco - aurum	TITLE PRODUCTION ANALYST	PATE OCTOBER 28, 1982

· Zavisor

DATE 11/8/82