

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- CARBON DIOXIDE		5a. Indicate Type of Lease State ☐ Fee ☒
2. Name of Operator HNG FOSSIL FUELS COMPANY		5. State Oil & Gas Lease No.
3. Address of Operator 811 DALLAS STREET, SUITE 1505, AMERICANA BLDG., HOUSTON, TEXAS 77002		7. Unit Agreement Name
4. Location of Well UNIT LETTER C 1980 FEET FROM THE WEST LINE AND 1045 FEET FROM THE NORTH LINE, SECTION 9 TOWNSHIP 29N RANGE 26E NMPM.		8. Farm or Lease Name T. L. ROACH
		9. Well No. 2
		10. Field and Pool, or Wildcat WILDCAT
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Colfax

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐
 OTHER ☐

PLUG AND ABANDON ☒
 CHANGE PLANS ☐
 OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
 COMMENCE DRILLING OPNS. ☐
 CASING TEST AND CEMENT JOB ☐
 OTHER ☐
 ALTERING CASING ☐
 PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

July 24, 1979 Set 727' of 9-5/8" O.D., 32.30#, H-40, S.T. & C., R-3 Surface casing - cemented with 350 sxs cement. Cement circulated.

August 15, 1979 Set 1919' of 7" O.D., 20.00#, K-55, S.T. & C., R-3 Production casing. Cemented with 150 sxs cement.

August 21, 1979 T.D. 3485' - plugged back with 100 sxs of cement. Pulled drill pipe up to 2700' and set a 50 sx cement plug - unable to pull out of plug. Backed off stuck drill pipe at 2202'.

August 23, 1979 Set 399' of 5" O.D., 13.00#, K-55, S.T. & C., R-3 Liner at 2189'. Tagged top of liner hanger at 1775' - cemented with 60 sxs cement. Well T/A.

November/1979 Drilled & reamed to 2164'. Perforated 1926'-2020' - well T/A.

PROPOSED: PBTD - 2164' - spot a 20 sx cement plug across perforations 1926' - 2020' from 2070' back to 1926', inside 5" O.D., Liner. Set a 20 sx cement plug from 100' back to surface.

(over)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Richard H. ChurchTITLE PRODUCTION ANALYSTDATE OCTOBER 28, 1982PROVED BY Carl S. S. S.

TITLE _____

DATE 11/8/82

CONDITIONS OF APPROVAL, IF ANY:

"Well bore will be filled with 10# fresh water mud between plugs".

Set a steel marker of at least 4" diameter, set in concrete, and extending at least four feet above mean ground level. The name; and number of the well and its location, (Unit letter, Section, Township, and Range) permanently engraved into the metal of the marker.