EN	ERGY MO. MINERALS DE	PAH	itae	í١
•				
	DISTRIBUTION			
	SANTA FE			L
	FILE .			ľ
	U.1.0.1.			l
	LAND OFFICE			ı

20.00			MORKAN LION DI	IVISION		
DISTA	INUTION		P. O. BOX 2088			Form C-103
SANTAFE		SANT	A FE, NEW MEXICO	97501		Revised 10-1-78
FILE .		7 · · · · · ·	. , a, men mexico	47301	····	
U.S.G.S.		7			5a. Indicate Ty	pe of Lease
LAND OFF	ICE	7			State X	Fee
OPENATO	7	7			5. State Oil & C	as Lease No.
					LG-4485	
					11111111	mm
ina wat	SUNDE	RY NOTICES AND RE	PORTS ON WELLS		(1111111)	
	USE "APPLICAT	TION FOR PERMIT -" (FORM	C-1011 FOR SUCH PROPOSALS.	MENT MESERVOIR.	(
1.	_				7. Unii Agreeme	int Name
ا ۱۳۰۰ ا	WELL	OTHER CARBON	DIOXIDE			
2. Name of Operat	tor				8, Form or Leas	e liame
HNG FO	SSIL FUELS CO	MPANY			State	
				· · · · · · · · · · · · · · · · · · ·		
J. Address of Ope		G-15- 1505 3	4 		9. Well No.	
SII Da.	mas Street,	Suite 1505, Amer	icana Bldg., Houst	on, Texas 77	002 1	
4. Location of We	11				10. Field and P	ool, or Wildcat
	Δ	660	North	660	7.72 7.22	
UNIT LETTER		DOU FEET PROM THE	North LINE AND	DOU PEET	Mildcat	mmmm
		_				
THE East	LINE, SECTI	10H 7 OWH!	SHIP 25N HANGE	24E	1MPM. (
		15. Elevation	(Show whether DF, RT, GR, e	ite.)	12. County	
		GR=612	2', DF=6130', RKB=	61311	Colfax	
18.	m					
	Check	Appropriate Box To	Indicate Nature of No	otice, Report of	r Other Data	
•	NOTICE OF I	NTENTION TO:	Į.	SUBSEQL	JENT REPORT OF	:
			·			N
PERFORM REMEDIA	AL WORK	PLUS AND	ABANDON THE REMEDIAL WO	••	ALTE	RING CASING
	75		-	}	i ·	1
TEMPORARILY ASA			COMMENCE DR	ILLING DPHS.	PCUE	AND ABANDONMENT [A]
PULL OR ALTER CA	ASIME I I				1	
		CHANGE P	LANS CASING TEST	AND CEMENT JOS .		
		CHANGE P	CASING TEST	AND CEMENT JOB		
•THER	·····	CHANGE P		AND CEMENT JOB		
•THER	. _		OTHER		<u> </u>	
ethen	posed or Completed O				uding estimated date of	starting any proposed
•THER	posed or Completed O		OTHER		uding estimated date of	starting any proposed
17. Describe Prop	posed or Completed O		OTHER		uding estimated date of	starting any proposed
17. Describe Propwork) SEE RU	posed or Completed On ULE 1703.	perations (Clearly state al	OTHER	persinens dases, incl		
17. Describe Propwork) SEE RU	TD - 2664 1.	perations (Clearly state al	OTHER	persinens dases, incl		
17. Describe Propuork) SEE Ru 9/15/79 8/31/79	TD - 2664' 653' of 13-3 to surface.	perations (Clearly state al	other	-3 surface c	asing set and	cemented back
17. Describe Propwork) SEE RU	TD - 2664" 653' of 13-3 to surface. 1794' of 9-9	3/8" O.D., 48.00	#, H-40, S.T.&C. R	-3 surface c	asing set and	cemented back
9/15/79 8/31/79 9/09/79	TD - 2664' 653' of 13-3 to surface. 1794' of 9-9 sxs. of Clas	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement +	#, H-40, S.T.&C. R. #, H-40, S.T.&C.,]	-3 surface c	asing set and	cemented back cemented w/265
17. Describe Propuork) SEE Ru 9/15/79 8/31/79	TD - 2664' 653' of 13-3 to surface. 1794' of 9-9 sxs. of Clas	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement +	#, H-40, S.T.&C. R. #, H-40, S.T.&C.,]	-3 surface c	asing set and	cemented back cemented w/265
9/15/79 8/31/79 9/09/79	TD - 2664' 653' of 13-1 to surface. 1794' of 9-1 sxs. of Clas	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug	#, H-40, S.T.&C. R. #, H-40, S.T.&C.,] 18% salt added. @ 1550' and cement	-3 surface coproduction cont sqz'd. Per	asing set and asing set and foration 1484'	cemented back cemented w/265 -1492' (GR)
9/15/79 8/31/79 9/09/79	TD - 2664': 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. C.	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug	#, H-40, S.T.&C. R. #, H-40, S.T.&C.,]	-3 surface coproduction cont sqz'd. Per	asing set and asing set and foration 1484'	cemented back cemented w/265 -1492' (GR)
9/15/79 8/31/79 9/09/79 5/04/80	TD - 2664 to surface. 1794 of 9-5 sxs. of Clas PBTD=1498 to sys. C. 1498 to sys.	perations (Clearly state al 3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 188 salt added. @ 1550' and cemental's CaCl2' and 10% No	-3 surface coproduction cot sqz'd. Per AC1 added.	asing set and asing set and foration 1484'	cemented back cemented w/265 -1492' (GR)
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80	TD - 2664' 653' of 13- to surface. 1794' of 9-! sxs. of Clas PBTD=1498'. W/100 sxs C: 1498'. Perforated 9	perations (Clearly state al 3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 1 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No	-3 surface coproduction cont sqz'd. Per AC1 added.	asing set and asing set and foration 1484' Drilled out ce	cemented back cemented w/265 -1492' (GR)
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13- to surface. 1794' of 9-! sxs. of Clas PBTD=1498'. w/100 sxs C. 1498'. Perforated 9	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casir Perfs open 1488	#, H-40, S.T.&C. R. #, H-40, S.T.&C.,] 18% salt added. @ 1550' and cement call and 10% No. 1% CaCl2' and 10% No. 1% from 1490'-1488 1-1490'- WELL TEMPO	-3 surface control of the sqz'd. Per ACl added. ' (GR). ORARILY ABAN	asing set and asing set and foration 1484' Drilled out ce	cemented back cemented w/265 -1492' (GR) ment to
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80	TD - 2664' 653' of 13- to surface. 1794' of 9-! sxs. of Clas PBTD=1498'. w/100 sxs C. 1498'. Perforated 9	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casir Perfs open 1488	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 1 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No	-3 surface control of the sqz'd. Per ACl added. ' (GR). ORARILY ABAN	asing set and asing set and foration 1484' Drilled out ce	cemented back cemented w/265 -1492' (GR) ment to
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + Set bridge plug lass H cement w/ 9-5/8" O.D. Casir Perfs open 1488 tubing set @ 1498	#, H-40, S.T.&C. R #, H-40, S.T.&C.,] 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No. ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of	-3 surface control of the sqz'd. Per ACl added. ' (GR). ORARILY ABAN class H ceme	asing set and asing set and foration 1484' Drilled out ce	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBID=1498'. w/100 sxs Cl 1498'. Perforated 9 PBID=1498'. lst plug - 4 ft. 3/sx. Di	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 18% salt added. @ 1550' and cemental CaCl2' and 10% No. 199 from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water	-3 surface comproduction compr	casing set and casing set and foration 1484' Drilled out ce DONED. Int mixed @ 16. bing out cemen	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13- to surface. 1794' of 9- sxs. of Clas PBTD=1498'. w/100 sxs Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 6 ft. 3/sx. Di 1498'-1398'.	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w.	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 188 salt added. @ 1550' and cement 18 CaCl2' and 10% No. ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water of 1398'. Pumped 109	-3 surface control of the sqz'd. Per ACl added. ' (GR). ORARILY ABAN class H ceme er. With tu 5 bbls of 10	easing set and easing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface.
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664 to surface. 1794 of 9-! sxs. of Clas PBTD=1498 to w/100 sxs Clas PBTD=1498 to surface. 1498 to sur	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w . Pull tubing to tubing set @ 100	#, H-40, S.T.&C. R #, H-40, S.T.&C., 1 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls wate 0 1398'. Pumped 10! ', pumped 40 sxs C	-3 surface comproduction contact added. ' (GR). ORARILY ABAN class H cemer. With tues to bols of 10 lass H cemen.	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w . Pull tubing to tubing set @ 100	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 188 salt added. @ 1550' and cement 18 CaCl2' and 10% No. ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water of 1398'. Pumped 109	-3 surface comproduction contact added. ' (GR). ORARILY ABAN class H cemer. With tues to bols of 10 lass H cemen.	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664 to surface. 1794 of 9-! sxs. of Clas PBTD=1498 to w/100 sxs Clas PBTD=1498 to surface. 1498 to sur	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w . Pull tubing to tubing set @ 100	#, H-40, S.T.&C. R #, H-40, S.T.&C., 1 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls wate 0 1398'. Pumped 10! ', pumped 40 sxs C	-3 surface comproduction contact added. ' (GR). ORARILY ABAN class H cemer. With tues to bols of 10 lass H cemen.	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w . Pull tubing to tubing set @ 100	#, H-40, S.T.&C. R #, H-40, S.T.&C., 1 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls wate 0 1398'. Pumped 10! ', pumped 40 sxs C	-3 surface comproduction contact added. ' (GR). ORARILY ABAN class H cemer. With tues to bols of 10 lass H cemen.	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w . Pull tubing to tubing set @ 100	#, H-40, S.T.&C. R #, H-40, S.T.&C., 1 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls wate 0 1398'. Pumped 10! ', pumped 40 sxs C	-3 surface comproduction contact added. ' (GR). ORARILY ABAN class H cemer. With tues to bols of 10 lass H cemen.	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w . Pull tubing to tubing set @ 100	#, H-40, S.T.&C. R #, H-40, S.T.&C., 1 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls wate 0 1398'. Pumped 10! ', pumped 40 sxs C	-3 surface comproduction contact added. ' (GR). ORARILY ABAN class H cemer. With tues to bols of 10 lass H cemen.	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casir Perfs open 1488; tubing set @ 1496; isplaced cement w. Pull tubing to tubing set @ 100 ement to surface.	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No. ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water of 1398'. Pumped 10%, pumped 40 sxs of 1398'. Pumped 10%. Pull tubing out of the same of the s	-3 surface comproduction control added. ' (GR). ORARILY ABAN class H cemer. With tustion to bols of 10 lass H cemen of hole. Fi	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casir Perfs open 1488; tubing set @ 1496; isplaced cement w. Pull tubing to tubing set @ 100 ement to surface.	#, H-40, S.T.&C. R #, H-40, S.T.&C., 1 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls wate 0 1398'. Pumped 10! ', pumped 40 sxs C	-3 surface comproduction control added. ' (GR). ORARILY ABAN class H cemer. With tustion to bols of 10 lass H cemen of hole. Fi	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casir Perfs open 1488; tubing set @ 1496; isplaced cement w. Pull tubing to tubing set @ 100 ement to surface.	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No. ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water of 1398'. Pumped 10%, pumped 40 sxs of 1398'. Pumped 10%. Pull tubing out of the same of the s	-3 surface comproduction control added. ' (GR). ORARILY ABAN class H cemer. With tustion to bols of 10 lass H cemen of hole. Fi	casing set and casing set and foration 1484' Drilled out ce DONED. The mixed @ 16. Bing out cemen # gel spacer to the mixed at 16.	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casir Perfs open 1488; tubing set @ 1496; isplaced cement w. Pull tubing to tubing set @ 100 ement to surface.	#, H-40, S.T.&C., P. #, H-40, S.T.&C., P. 18% salt added. @ 1550' and cemental CaCl2' and 10% No. Ing from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water to 1398'. Pumped 10. ', pumped 40 sxs C. Pull tubing out of the control	-3 surface comproduction control sqz'd. Per ACl added. ' (GR). ORARILY ABAN class H ceme er. With tust bbls of 10 lass H cemen of hole. Fi	casing set and casing set and casing set and continuous foration 1484' Drilled out cent mixed @ 16. bing out cent mixed at 16. ll Casing to set	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06 urface with
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + 1 Set bridge plug lass H cement w/1 9-5/8" O.D. Casir Perfs open 1488; tubing set @ 1496; isplaced cement w. Pull tubing to tubing set @ 100 ement to surface.	#, H-40, S.T.&C. R. #, H-40, S.T.&C., 18% salt added. @ 1550' and cement 1% CaCl2' and 10% No. ng from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water of 1398'. Pumped 10%, pumped 40 sxs of 1398'. Pumped 10%. Pull tubing out of the same of the s	-3 surface comproduction control sqz'd. Per ACl added. ' (GR). ORARILY ABAN class H ceme er. With tust bbls of 10 lass H cemen of hole. Fi	casing set and casing set and casing set and continuous foration 1484' Drilled out cent mixed @ 16. bing out cent mixed at 16. ll Casing to set	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664 to surface. 1794 of 9-1 sxs. of Clast PBTD=1498 to w/100 sxs. Clast PBTD=1498 to the surface of the system of the syst	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + Set bridge plug lass H cement w/ 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w Pull tubing to tubing set @ 100; ement to surface.	#, H-40, S.T.&C., P. #, H-40, S.T.&C., P. 18% salt added. @ 1550' and cemental CaCl2' and 10% No. Ing from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water to 1398'. Pumped 10. ', pumped 40 sxs C. Pull tubing out of the control	-3 surface comproduction control sqz'd. Per ACl added. ' (GR). ORARILY ABAN class H ceme er. With tust bbls of 10 lass H cemen of hole. Fi	casing set and casing set and casing set and continuous foration 1484' Drilled out cent mixed @ 16. bing out cent mixed at 16. ll Casing to set	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06 urface with
9/15/79 8/31/79 9/09/79 5/04/80 5/10/80 5/21/80	TD - 2664' 653' of 13-3 to surface. 1794' of 9-3 sxs. of Clas PBTD=1498'. w/100 sxs. Cl 1498'. Perforated 9 PBTD=1498'. lst plug - 4 ft. 3/sx. Di 1498'-1398'. 2nd plug - 4 ft. 3/sx. Ce	3/8" O.D., 48.00; 5/8" O.D., 36.00; ss "H" cement + Set bridge plug lass H cement w/ 9-5/8" O.D. Casin Perfs open 1488; tubing set @ 1498; isplaced cement w Pull tubing to tubing set @ 100; ement to surface.	#, H-40, S.T.&C., P. #, H-40, S.T.&C., P. 18% salt added. @ 1550' and cemental CaCl2' and 10% No. Ing from 1490'-1488 '-1490'- WELL TEMPO 8', pumped 40 sxs of with 8.09 bbls water to 1398'. Pumped 10. ', pumped 40 sxs C. Pull tubing out of the control	-3 surface control of the sqz'd. Per ACl added. '(GR). ORARILY ABAN class H ceme er. With tust bbls of 10 lass H cemen of hole. Fi	casing set and casing set and casing set and control 1484' Drilled out centrol poner. DONED. Int mixed @ 16. bing out cemen # gel spacer to the mixed at 16. ll Casing to set to	cemented back cemented w/265 -1492' (GR) ment to 4 PPG, 1.06 t plug set @ o surface. 4 PPG, 1.06 urface with



November 9, 1982

For: Mr. James Black

HNG Fossil Fuels

811 Dallas St., Suite 1505 American Bldg.

Houston, TX 77002

Re: State #1

Sec. 9 - 25N - 24E

Colfax County, New Mexico

The purpose of this letter is to provide an affidavit stating the above referenced well was plugged to abandon.

WELL DATA:

Casing: 9 5/8", 36 lb/ft. Tubing: 2 7/8", 6.5 lb/ft.

lst Plug:

Tubing set @ 1498'
Pumped 40 sks. Class H Cement mixed @ 16.4 PPG, 1.06 ft3/sk.
Displaced cement with 8.09 BBLS water.
With tubing out Cement plug set @ 1498' - 1398'.

Pull tubing to 1398'.
Pumped 105 BBL of 10# gel spacer to surface.

2nd Plug:

Tubing set @ 100 ft.
Pumped 40 sks Class H Cement mixed at 16.4 PPG, 1.06 ft3/sk.
Cement to surface.
Pull tubing out of hole.
Fill casing to surface with cement.

Halliburyon Operator



P.O. BOX 84737 DALLAS, TEXAS 75284

DIRECT ANY CORRESPONDENCE TO

P.O. DRAWER 1431
DUNCAN OKLAHOMA 73536

PAGES

PAGE 1 OF

INVOICE

NO.

057431

FORM 1906 R-6					ONCAN, OKI	LAHUM	4 /3536					L L	10140	ı
ELL NO. AND FARM				1	UNTY		STAT		•	DA				
HARGE TO	7070				colfax	0	WNER Y	1. m.		انما	I	3 - 82		
4NG F	ossil fu-	د/ح	-				Sam C			ONL				
				/)						OCATIO		CODE	
O / DA	Ilas ST	<u> 2u</u>	Tes	05/M	MERICAN	BIOG !	Je / Te c	ر بدرس	11 Sex	<u> </u>	Lam	AR C.	o. Soul	115
Hous	TON, 7	K	<u>,</u>		7002		o. 7	۲.		2	Hou	g07-n	Nr 50	335
ļ	· /									2	OCATIO	Y	CODE	
j J						ō	LOC.				KMATEH	IAL D		· · · · · · · · · · · · · · · · · · ·
9 7											ET NO.	R-	178801	
,						į	ELL TYPE						ļe e	ODE
) 1						1.	Wild C	POSE OF JO	B					UC
TERMS:	NET CHARGED AP	20TH O	F FOLLO	WING MON	TH. INTEREST		Retrie.	v + P	ack.	x +	Bri	dy	Plue	
			, , , , , , ,	NOM DATE	·	į.	PTH						•	
PRICE	SECONDARY REF.	CODE	E		ESCRIPT			UNI	TS 1	רואט	'S 2	UNIT		
REFERENCE	OR PART NO.	L C	-}- -					QTY.	MEAS.	QTV.	MEAS.	PRICE	AMOUN	
000-117		1 0	MIL	EAGE				183	mj		!	2.15	393	45
009-D19		1 6	· Pu	mp C	hg			1458	fr		1		1258	80
2040-410		11	D	a live	KY Ch	ARG	د	1	DIR		 	27,00	276	200
509-554		18		-	etan C		,	3:	3 SK3		1	440	li	80
160-115		12			Age o	- •	. 7		mi		l I	.90	164	.i
102-053		17	1		TOR II			_	מיוע	, , ,,)	1		200	
									- -	. <u></u>	1		20	
				e					l l		1	·		
		11	1			 	· · · · · · · · · · · · · · · · · · ·				<u>'</u>			
		4 4	100		- 		4	1	1		1 0			-
		4 D	Bul	KIKH	ot # 178	70/	Allac	hæ t	-	· · · · · · · · · · · · · · · · · · ·	1		1126	46
		+	+		<u></u>				1	_	1			
	·	++	 				· · · · · · · · · · · · · · · · · · ·		1		<u>i</u>			
-			ļ						<u> </u>		i			<u> </u>
			 						-		1		ļ	
			SERVI	CE CHARGE	ON MATERIAL	SRETUR	1ED		CU.		1			
		Ш	SERVI	CE CHARGE	<u>.</u>	·.			CU.		1			
					TOTAL WEIGHT		LOADED MILES		TON		1			
					Ţ	AXREF	ERENCES				S115	TOTAL	3631	21
S JOB SATISFACTO	RILY COMPLETED!											TAX		
S OPERATION OF E	QUIPMENT SATISFACT	TORY1.						·		·····		TAX		
S PERFORMANCE O	F PERSONNEL SATISF	ACTOR	ł¥1							./.		TAX		
Sm	w/D	lo	26		-al	Cart	Di	cler	1+	<u>H.D.</u>	The	BOTAL		<u> </u>
// *	Customer or His A	igent			•		Halliburton	Operator	_	•			ر اح	



ORM 1906 R-3

WORK ORDER CONTRACT AND PRE-TREATMENT DATA

ATTACH TO	Acausi
INVOICE & TICKET	NO. 057431

DISTRICT LIVE VAL					DATE	10-3-	87
THE SAME AS AN INDEPENDENT CONTRACTOR TO:	_	_				DELIVER A	ND OPERATE
AND DELIVER AND SELL PRODUCTS, SUPPLIES, AND MATERIAL	S FOR THE	PURPOSE	OF SERVIC	NG			
WELL NO. # LEASE STATE		SEC.	9	TWP	25~	RAN	IGE 14 =
TELD Wilden COUNTY COLFAC ST							Fuels
THE FOLLOWING INFORMATION WAS	FURNISHE	· · · · · · · · · · · · · · · · · · ·	E CUSTO	MER OR	HIS AGE	VT.	
ORMATION		NEW	WEIGHT	SIZE	. FROM	то	MAX. ALLOW. P.S.I.
ORMATION FROM TO	CASING		36	95	GL	1498	
ACKER: TYPESET AT	LINER			•			
OTAL DEPTH 14/98 MUD WEIGHT	TUBING		6.5	22	RL	1498	
ORE HOLE	OPEN HOL	E		'			янот я/г т.
NITIAL PROD: OILBPD, H±OBPD, GASMCF	PERFORAT	IONS			1488	1490	
RESENT PROD: OILBPD, H2OBPD, GASMCF	PERFORATI	ONS					
	PERFORATI	ONS					
REVIOUS TREATMENT: DATETYPE			MATERIA	Ls			
REATMENT INSTRUCTIONS: TREAT THRU TUBING ANNULUS [] CA	SING TUB	ING/ANNI	JLUS HY	PRAULIC H	ORSEPOWE	R ORDERED	
P7A 40 SKS AT 1498	1298	10f	100	Ben7	ivait-	Gel Il	0
405Kr Hcm7 HT 100' To Top	of Sul	fac	٧				
/							
							···
USTOMER OR HIS AGENT WARRANTS THE WELL IS IN PROPER CONDITIO	N TORECEIVE	E THE PRO	DUCTS, SUP	PLIES, MAT	ERIALS, AND	SERVICES	
THIS CONTRACT MUST BE As consideration, the above-named Customer agrees:	SIGNED BEFORE	E WORK IS O	COMMENCED				
(a) To pay Halliburton in accord with the rates and terms stated in Halliburton's current pr	rice lists.						

- (b) Halliburton shall not be responsible for and Customer shall secure Halliburton against any liability for damage to property of Customer and of the well owner (if different from Customer), unless caused by the willful misconductor gross negligence of Halliburton, this provision applying to but not limited to subsurface damage arising from subsurface damage.
- (c) Customer shall be responsible for and secure Halliburton against any liability for reservoir loss or damage, or property damage resulting from subsurface pressure, losing control of the well and/or a well blowout, unless such loss or damage is caused by the willful misconductor gross negligence of Halliburton.
- (d) Customer shall be responsible for and secure Halliburton against any and all liability of whatsoever nature for damages as a result of subsurface trespass, or an action in the nature thereof, arising from a service operation performed by Halliburton hereunder.
- (e) Customer shall be responsible for and secure Halliburton against any liability for injury to or death of persons, other than employees of Halliburton, or damage to property (including, but not limited to injury to the well), or any damages whatsoever, irrespective of cause, growing out of or in any way connected with the use of radioactive material in the well hole, unless such damage shall be caused by the willful misconduct or gross negligence of Halliburton.
- (I) Halliburton makes no guarantee of the effectiveness of the products, supplies or materials, nor of the results of any treatment or service.
- (g) Customer shall, at its risk and expense, attempt to recover any Halliburton equipment, tools or instruments which are lost in the well and if such equipment, tools or instruments are not recovered, Customer shall pay Halliburton its replacement cost unless such loss is due to the sole negligence of Halliburton. If Halliburton equipment, tools or instruments are damaged in the well, Customer shall pay Halliburton the lesser of its replacement cost or the cost of repairs unless such damage is caused by the sole negligence of Halliburton. In the case of equipment, tools or instruments for marine operations, Customer shall, in addition to the foregoing, be fully responsible for loss of or damage to any of Halliburton's equipment, tools or instruments which occurs at any time after delivery to Customer at the landing until returned to the landing, unless such loss or damage is caused by the sole negligence of Halliburton.
- (h) Because of the uncertainty of variable well conditions and the necessity of relying on facts and supporting services furnished by others. Halliburton is unable to guarantee the accuracy of any chart interpretation, research analysis, job recommendation or other data furnished by Halliburton. Halliburton personnel will use their best efforts in gathering such information and their best judgment in interpreting it, but Customer agrees that Halliburton shall not be responsible for any damages arising from the use of such information except where due to Halliburton's gross negligence or willful misconduct in the preparation or furnishing of it.
- (i) Halliburton warrants only title to the products, supplies and materials and that the same are free from defects in workmanship and materials. THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE WHICH EXTEND BEYOND THOSE STATED IN THE IMMEDIATELY PRECEDING SENTENCE. Halliburton's liability and Customer's exclusive remedy in any cause of action (whether in contract, fort, breach of warranty or otherwise) arising out of the sale or use of any products, supplies or materials is expressly limited to the replacement of such products, supplies or materials on their return to Halliburton's option, to the allowance to the Customer of credit for the cost of such items. In no event shall Halliburton be liable for special, incidental, indirect, punitive or consequental damages.
- (i) Upon Customer's default in payment of Customer's account by the last day of the month following the month in which the invoice is dated. Customer agrees to pay interest thereon after default at the highest lawful contract rate applicable but never to exceed 18% per annum. In the event it becomes necessary to employ an attorney to enforce collection of said account. Customer agrees to pay all collection costs and attorney fees in the amount of 20% of the amount of the unpaid account.
- (k). This contract shall be governed by the law of the state where services are performed or equipment or materials are furnished
- (II) Halliburton shall not be bound by any changes or modifications in this contract, except where such change or modification is made in writing by a duly authorized executive officer of Halliburton

DATE 11-3-82-11-4-4

HALLIBURTON SERVICES

JOB LOG

CUSTOMER HNG FOSSIL FUELS PAGE NO.

FORM 2013 R-2 PRESSURE (PSI) CHART NO. DESCRIPTION OF OPERATION AND MATERIALS TUBING | CASING 05:00 Called out on Loc wasting on Rig 09:00 15:30 Release RTTS Rig Vull Tab + Packs Packer pol of Ital Attack Overshot pod not Retrive bridge plus
Run in Tob To Kelvieve Vridge play 16:15 11:30 Tubing on bottom shot down go to Muld 17:30 STORT HO TO 07:37 STALT CIRCULATION 07:48 48 200 Shut down Rig Pull 4 Joint Tol 02:53 53 300 08:52 08:54 2.55 Start Displ 150 Shut down CmT Plug AT 1498 TO 1398' 08:56 8.04 200 Aig Pull 4 soint Tub 570,7 10 # g = 1 7 10:14 0 Shut down get plug AT 1398'- 0' 8 10:36 104 100 fig pull tubing 70 100' 9 12:08 0 Shot down + washup Pluga 1/00'-0' 10 12:10 2 7.55 150 Job Complete Thonk You!

_		TON SE			•	HALLIBURTON DIVISION _	Wick	ىلىر	- K	£			
	B S	UMM	AR'	Y	•	HALLIBURTON LOCATION	La	nar	. Co.		FI	LLED ON CKET NO	57431
							L DATA	-					
.0	Wilk	Cal			_sec9	TWP	RNG. J		COUNTY	Colf	Y	STATE _	17.19.
MATIC	N NAME			TYP	«			NEW	WEIGHT	SIZE	FROM	TO	MAXIMUM PE
				FROM			CASING		36.00	95	CL	1498	
				BFO.			LINER						
							TUBING		6-5	22	שא	1498	·
PLETI				/PE			OPEN HOLE				 		SHOTS/FT.
KERT				SET /			PERFORATI				1488	1490	
				PRESSURE			PERFORATI					 	
, DAT	^			TOTAL	DEPTH	JOI	B DATA	ONS		L		_1	
		TOOLS A	AND AC	CESSORIES			CALLED OU	Ť	ON LOC	ATION	JOB STARY	10	B COMPLETED
	TYPE A	ND SIZE		QTV.		AAKE	DATE //-	3 - 6	DATE	1-2-8	2 DATE //-	3 - 81 0	ATE
AT CO	LLAR										TIME /		ME
AT 5H	o#							······			ND SERVIC		
K 5H) E								NAME		UNIT NO.	& TYPE	LOCATION
TRALI	ZERS						5 1	all	icll		8339	Lo	mar Co
TOM P	LUG								42/4		3251		11 11
PLUG				<u> </u>					re	_	1537		1 /1
0				<u> </u>					· k.5				UG TON HS.
KER													<i>V</i>
E 71													
			MATERI	ALS							_		
AT. FL	.vib			DENSITY		LB/GAL.ªAPI							
L. FLI		··· - · · · · · · · · · · · · · · · · · · ·		_DENSITY		LB/GAL. API					4		
P. TYP													****
P. TYP											4		
TYPE				AL			-						MAA
TYPE				AL							-		WV ~
7 TYPE	NT TYPE	· · · · · · · · · · · · · · · · · · ·		AL			DEPARTMENT		<u> </u>				(/x /
	TYPE			AL						N	RMS	. 4	
	S ADD,TYPE			LB.							29810		9-1 405
	GENT TYPE_			··· <u></u>	'^"				17.7.	l	7.4. 0		107
	_				in								
AKER	TYPE		GAL	LB	IN		JOB DONE TH	RU; T	Jaine 🔯	c.	ASING [ANNULUS [TBG./ANN.
KING	AGENT TYPE				ALLB				1	_	د سیست	9 J	•
PAC	BALLS TYPE_			a	TY		CUSTOMER Representa	TIVE	XX	m	-46	Mex	
·~							HALLIBURTO	. //	/	2	· —		
K R	·						OPERATOR_	· L	Heil	Die	tech	COPIES REQUESTS	KD
- · · · · · · · · · · · · · · · · · · ·			T	1	Т	CEME	NT DATA	_4	St.	13	gol		<u> </u>
	NUMBER OF SACKS	TYPE	API CLASS	BRAND	BULK			ADDIT	rives	•		CU.FT./SI	MIXED LBS./GAL.
	40	647	L		BUIL		n4 := :=	·					
	93	Gel	H_	Hallibis.			270 n 4				·····	1.06	16.4
	40	CMT	11	TT SELLES HIS		····	11					10-10	GA /
		<u> </u>	'		-11						····	1.00	16.4
\dashv		· · · · · · · · · · · · · · · · · · ·	1										+
		PRESSU	JRES IN	PSI	·	SUMMAR	YGal Plus	<u> </u>	,	VOL	UMES		
ULAT	NG			HSPLACEMENT_		 '	PRE-MON: 88	a A L .	104	1.97	TYPE	·	
KDG				1AXIMUM2_	5 D		LOAD & BKON:	■■	3 A L			D: BBL,-GAL,	
RAGE	100		FRACT	TURE GRADIENT	·		TREATMENT: B	B L,-GA	د			SPL: BBL,-GAI	8.09
'-INI I		HYDRALII	PMIN.	SEPOWER	_ 15-MIN	·	CEMENT SLURR	Y: 05	LGAL	7.5	<u> </u>	7.5 .5	
				SEFUMER		•	FOTAL VOLUME		GAL				
		AVERAGE		S IN BPM	. USED		1	,	_	REMA			1 .
							, ,		_,	4∠1	Tries	_ 1.4	ridga



Statement ...

BULK MATERIALS DELIVERY AND TICKET CONTINUATION

FOR INVOICE AND OS74/31

DATE	CUSTOMER ORDER NO.			WELL NO. AND FARM COUN					STATE					
11-3-81 CHARGE TO				OWNER CONTRACT				fax	n.m					
								CONTRA	CTOR			No. B	1788	01
H W G F	osrill	ب	•	5		Seme.	· · · · · · · · · · · · · · · · · · ·	LOCATIO	N CODE	PREI	ARED 8	,	1100	0 1
						HougeTen KS		503	355	- A	. Di	27011	.	
CITY & STATE						Springer N.19, 10E		384J		t t	EIVED BY	·		
PRICE REFERENCE	SECONDARY REF. OR PART NO.	со	DE			DESCRIPTION		UNITS	1	1 UNITS 2		UNIT PRICE	AMOUNT	
									MEAS.	QTY.	MEAS.			
504-043		12	8		Y	cement		80	SKA		-	6.68	534	40
		+	-						-		-			
		$\dagger \dagger$									-			
•											-			
		1									1			
			_								-	<u></u>		
														
									+		1			
		\Box												
		\Box		,						· · ·	-			
						· · · · · · · · · · · · · · · · · · ·					i			
	····								-	 -	-			
		+-												
	. 12 11.	+				· · · · · · · · · · · · · · · · · · ·				· · · · · · · · · · · · · · · · · · ·	<u> </u>			
		$\dagger \dagger$			-						1			
		_	¥.	Returned Mileage Charge		TOTAL WEIGHT	LOADE	D MILES	TON	i MILES				-
				SERVICE C	HAR	GE ON MATERIALS RETURNED			CU.	FEET				,
500-207				SERVICE C	HAR	GE			cu.	FEET &	30	.95	Z	00
500-207 500-314				Mileage Charge		SZO TOTAL WEIGHT	LOADE	& Z D MILES	TON	MILEY	88	,75	76 516	06
D 1	, ,		_	· · · · · ·										1,1