

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
Sauble	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Wildcat	
12. County	
Colfax	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Carbon Dioxide & Hydrocarbons	
2. Name of Operator	
HNG FOSSIL FUELS COMPANY	
3. Address of Operator	
P. O. Box 1188, Houston, Texas 77001	
4. Location of Well	
UNIT LETTER	H
1980	North
FEET FROM THE	660
LINE AND	FEET FROM
East	35
THE	LINE, SECTION
35	TOWNSHIP
27 N	RANGE
24 E	NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)	
6390 GR	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/21/79: T.D. 613. Set 589' of 9 5/8" 32.30 lb. H-40 ST&C R-3 casing at 601 KB. Cemented with 175 sacks Halliburton Class H cement with 12 1/2 lbs. per sack gilsonite and 3% calcium chloride. Tail in with 200 sacks Halliburton Class H cement with 3% calcium chloride. Cement circulated. P.D. 12:00 noon 9/21/79. W.O.C. Resumed drilling 6:30 a.m. 9/22/79.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Richard Boehm TITLE Administration Manager DATE 9/25/79

APPROVED BY Carl Lekvåg TITLE SENIOR PETROLEUM GEOLOGIST DATE 9/28/79

CONDITIONS OF APPROVAL, IF ANY: