

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-007-20067
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Chalfont-Kaiser
8. Well No. 1-Y
9. Pool name or Wildcat Wildcat

<p>SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</p>	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator PEMCO (Vermejo Park Corp.)	
3. Address of Operator Route 1, Box 68, Cimarron, NM 87714	
4. Well Location Unit Letter <u>O</u> : <u>740</u> Feet From The <u>South</u> Line and <u>1640</u> Feet From The <u>East</u> Line Section <u>13</u> Township <u>29 N</u> Range <u>21 E</u> NMPM Colfax County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6786 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/10/90 Pull tubing and packer. No pressure. RIH with tubing. Set 240' plug 3220 to 2980 with 22 sks class A cement @ 15.6 ppg.

4/11/90 Fill well bore with 8.6 ppg Bentonite gel mud.

4/12/90 Free point 4 1/2" casing and cut @ 1510. Pull casing. Set 150' plug 1510 to 1360 with 48 sks class A cement @ 15.6 ppg.

4/13/90 Set cement retainer @ 285' with 15 sks class A cement below retainer and 120' plug 285 to 165 with 36 class A cement @ 15.6 ppg. Set 50' surface plug with 15 sks class A cement @ 15.6 ppg. Cut casing 3' below surface and set marker. Pit filled and location leveled.

At the request of Vermejo Park Corp., new owner of the Kaiser property (PEMCO), Pennzoil Exploration and Production Co. has plugged and abandoned this well as shown.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE Operations Superintendent DATE 4/17/90

TYPE OR PRINT NAME L. D. Williamson TELEPHONE NO. 505-376-2817

(This space for State Use)

APPROVED BY R. E. Johnson DATE 4-26-90

CONDITIONS OF APPROVAL, IF ANY: