

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-007-20083

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER Coal Methane

2. Name of Operator

Pennzoil Exploration and Production Company

7. Lease Name or Unit Agreement Name

Van Bremmer Canyon
3018

8. Well No.

253B

3. Address of Operator

P.O. Box 2967, Houston, Texas 77252

9. Pool name or Wildcat

Wildcat

4. Well Location

Unit Letter B : 300 Feet From The North Line and 2214 Feet From The East Line

Section 25

Township 30N

Range 18E

NMPM

Colfax

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7797 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Drilling completed ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-21-89 Spud, Drill 14 3/4" hole to 46'. Set and cement 2 jts (46'), 42 lb. H-40, ST&C conductor w/75 sks class G w/3% CaCl @ 15.8 ppg. Cement to surface.

5-22-89 Drill 11" hole to 331'. Set and cement 12 jts (326') 8 5/8", 24 lb, J-55, ST&C casing w/220 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface.

7-24-89 Test casing and BOP w/600 psi. for 30 minutes. No pressure drop.

7-31-89 Drill 7 7/8" hole to 2285'.

8-01-89 Set and cement 85 jts (2260') 5 1/2", 17 lb. J-55, LT&C casing w/500 sks sil- icalite @ 11.0 ppg. Bumped plug w/1000 psi.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE Operations Superintendent DATE 8-8-89

TYPE OR PRINT NAME L. D. Williamson

TELEPHONE NO. 505-376-2817

(This space for State Use)

APPROVED BY Reg. E. Johnson DISTRICT SUPERVISOR DATE 8-9-89

CONDITIONS OF APPROVAL, IF ANY: