

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-007-20084

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Van Bremmer Canyon  
3019

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☐

OTHER Coal Methane

2. Name of Operator

Pennzoil Exploration and Production Company

8. Well No.

321K

3. Address of Operator

P.O. Box 2967 Houston, TX 77252

9. Pool name or Wildcat

Wildcat

4. Well Location

Unit Letter K : 1696 Feet From The west Line and 1867 Feet From The south Line

Section 32

Township

30N

Range

19E

NMPM

Colfax

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7641 GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Completed drilling ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-29-89 Spud, drill 14 3/4" hole to 43'. Set and cement 2 jts (43') of 11 3/4", 43 lb/ft, H-40, ST&C conductor w/60 sks class G w/3% CaCl W.O.C. 4 hrs. Drill 11" hole to 106'.

5-30-89 Drill 11" hole to 335'. Set and cement 12 jts (330') 8 5/8", 24 lb, J-55, ST&C casing w/227 sks class G w/2% CaCl @ 15.8 PPG. Bump plug w/500 psi @ 1530. Cement to surface.

6-8-89 Test casing and BOP w/600 psi for 30 mins. No pressure drop.

6-10-89 Drill 7 7/8" hole to 2125 TD and LOG.

6-11-89 Run and cement 79 jts (2085') 5 1/2, 17 lb. J-55, LT&C w/304 sks, class B silicalite cement @ 11 ppg. returns to surface. Bump plug w/1000 psi. Well shut in waiting on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE OPERATIONS Supt DATE 6-29-89

TYPE OR PRINT NAME LARRY D. WILLIAMSON

TELEPHONE NO. 505-376-2917

(This space for State Use)

DISTRICT SUPERVISOR

APPROVED BY [Signature] TITLE \_\_\_\_\_ DATE 7-14-89

CONDITIONS OF APPROVAL, IF ANY: