

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

Santa Fe, New Mexico 87504-2088

AUG 3 1989

OIL CONSERVATION DIV.

WELL API NO.

30-007--20086

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Van Bremmer Canyon  
3019

8. Well No.

322-D

9. Pool name or Wildcat

Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT'  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☐

OTHER Coal Methane

2. Name of Operator

Pennzoil Exploration and Production Company

3. Address of Operator

P.O. Box 2967, Houston, TX 77252

4. Well Location

Unit Letter D : 1254 Feet From The West Line and 1053 Feet From The North Line

Section 32

Township 30N

Range 19E

NMPM Colfax

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7638 GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Drilling completed ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-04-89 Spud. Drill 14 3/4" hole to 43'.

6-05-89 Set and cement 2 jts (42.65') 11 3/4", 42 lb. H-40 ST&C conductor w/67 sks class G w/3% CaCl @ 15.8 ppg. Cement to surface.

6-06-89 Drill 11" hole to 335'. Set and cement 12 jts (330') 8 5/8", 24 lb. J-55 ST&C casing w/195 sks class G w/2% CaCl @ 15.8 ppg. Plug did not bump. 19 bbls cement to surface.

7-20-89 Test BOP and casing w/600 psi for 30 minutes. No pressure drop.

7-21-89 Drill 7 7/8" hole to 2200'.

7-23-89 Set and cement 77 jts (2077.05') 5 1/2", 17 lb. J-55 LT&C casing w/315 sks silicalite @ 11 ppg. Bumped plug w/1000 psi. Cement to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE Operations Superintendent DATE 8-1-89

TYPE OR PRINT NAME L. D. Williamson

TELEPHONE NO. 505-376-2817

(This space for State Use)

APPROVED BY R. E. Johnson TITLE DISTRICT SUPERVISOR DATE 8-3-89

CONDITIONS OF APPROVAL, IF ANY: