

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

RECEIVED
CONSERVATION DIVISION
Santa Fe, New Mexico 87504-2088

JUL 10 1989

OIL CONSERVATION DIV

WELL API NO.

30-007-20087

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Van Bremmer Canyon

2919

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER Coal Methane

2. Name of Operator

Pennzoil Exploration & Production Company

8. Well No.

041-D

3. Address of Operator

P.O. Box 2967, Houston, Texas 77252

9. Pool name or Wildcat

Wildcat

4. Well Location

Unit Letter D : 63 Feet From The West Line and 479 Feet From The North Line

Section 4

Township 29N

Range 19E

NMPM

Colfax

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7538 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☒

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Drilling completed ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-06-89 Spud

6-07-89 Drilled 14 3/4" hole to 46.5'. Set & cement 2 jts (45.5') 11 3/4", H-40, 42 lb. ST&C w/72 sks class G w/3% CaCl @ 15.8 ppg. Cement to surface.

6-08-89 Drilled 11" hole to 335'. Set and cement 12 jts (330') 8 5/8", 24 lb. J-55, ST&C w/95 sks class G w/2% CaCl @ 15.8 ppg. Bump plug w/500 psi. Cement circulated to surface.

6-27-89 Test casing & bop w/600 psi. No pressure drop.

6-30-89 Drill 7 7/8" hole to 2130' and run logs.

7-01-89 Set and cement 75 jts (2035.47') 5 1/2", 17 lb. J-55, LT&C casing @ 2034' w/292 sks silicalite cement @ 11.0 ppg. Circulated 50 bbls. of cement to surface. Bump plug w/1000 psi.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE Operations Supt. DATE 7-6-89

TYPE OR PRINT NAME L. D. Williamson

TELEPHONE NO. 505-376-2817

(This space for State Use)

APPROVED BY [Signature] DISTRICT SUPERVISOR DATE 7-14-89

CONDITIONS OF APPROVAL, IF ANY: