CONDITIONS OF APPROVAL, IF ANX

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

12. Describe Proposed or Completed Operations (Clearly state all perinent details, and give perinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. H-40, ST&C conductor w/80 sks class G w/3% CaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-55 ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Thereby certly that the information should be best of my knowledge and belief. SHONATURE L. D. Williamson THE Operations Superintendent DATE THE OPERATINAME L. D. Williamson THE DEPHONE MS 05-376-28	District Office	2.0267, 3.12.01.22 2.00 3.01.2.2.2.3			Keybed 1-1-	0,7
Santa Fe, New Mexico 87504-2088 Solidate Type of Last Tart FEE Solidate Type of Last Tart FEE Solidate Type of Last Tart FEE Solidate Rd, Alled, NM 17410 6. Sale Oil & Gul Last Tart FEE Solidate Rd, Alled, NM 17410 6. Sale Oil & Gul Last Tart FEE Solidate Rd, Alled, NM 17410 6. Sale Oil & Gul Last Tart FEE Solidate Type of Last Tart FEE Solidate Rd, Alled, NM 1410 FEE Solidate Rd, Alled, NM	-DISTRICT I P.O. Box 1980, Hobbs, NM 88240					
STATE STATE STATE STATE STATE SOURCE AND REPORTS ON WELLS	DISTRICT II P.O. Drawer DD. Artesia NM \$8210				e252	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM KOR PROMOSALS TO DRILL OR TO DEEPEN OR PULG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PEMBY" DIFFERENT RESERVOR. USE "APPLICATION FOR PEMBY" 2918 1. Type of Wall: CAN	DISTRICT III				STATE	FEE X
CONNOTUSE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. US: APPLICATION FOR PERMIT	TWO KO BIZZA KE, AME, TWI \$7410			d. Sche Oil & Cit I		
DIFFERENT RESERVOR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS) 1. Type of Wall:	SUNDRY NOT	TICES AND REPORTS ON WE	LLS			
1. Figs of Well: Construction	DIFFERENT RESE	ERVOIR. USE "APPLICATION FOR PE		L .	-	
2 Name of Operhate Pennzoil Exploration and Production Company 3. Address of Operhate P.O. Box 2967, Houston, Tx 77252 4. Well Localize Uals Latter D: 619 Feet From The North Line and 28 Feet From The West Line Section I Towaship 29N Range 18E NATH Colfax County 10. Detartion (Show whether DF, RKB, RT, GR, etc.) 7992 GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OFNS. X PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OFNS. X PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OFNS. X PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OFNS. X PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OFNS. X PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OFNS. X PLUG AND ABANDONMENT PULL OR ALTER CASING COMMENCE DRILLING OFNS. X PLUG AND ABANDONMENT OFTER: Drilling completed 12. Describs Proposed or Completed Operations (Clearly state all periband details, and give periband data, including a straing any proposed world). SEE MULE 1103. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. H-40, STEGC conductor w/80 sks class G w/37. GaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-5: STEGC casing w/170. sks class G w/27. Cacl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Drill 7 7/8" hole to 2588'. Logging. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Ilmany sently that the later parks and strain that Thereby sently that the later parks and strain that The perfect of the State Uag The perfect of State Uag The perfec	1. Type of Well:			D. Comments of the Comment of the Co	., ,	
Pennzoll Exploration and Production Company 1. Address of Operator 1. P. O. Box 2967, Houston, Tx 77252 4. Wall Leastion Ualt Letter D : 619 Feet From The North Lise and 28 Feet From The West List Section I Township 29N Range 18E NAMEM Colfax County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING CHANGE PLANS CASING COMMENCE DEPLLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CHANGE PLANS CHANGE DEPLLING OPNS. PLUG AND ABANDONMENT 12. Describe Proposed or Completed Operations (Clearly state all peribers detail), and give peribers detail, including entimeted date of staning any proposed world) SEE RULE 1103. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. 8/21/89 Test Casing with 170 seks class G w/2% Cacl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing 6 BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the later of my knowledge and bailed. 1 Intervolve world you have later of the		OTHER Coal	Methane			
P. O. Box 2967, Houston, Tx 77252 9. Foot larne or Wildcat P. O. Box 2967, Houston, Tx 77252 9. Foot larne or Wildcat Wildcat	· · · · · · · · · · · · · · · · · · ·	ion and Production Com	nany			
Well Location Unit Letter D	3. Address of Operator ·				leat	
Usil Letter D : 619 Feet From The North Line and 28 Feet From The West Lite Section I Township 29N Range 18E NMPM Colfax County 10. Pervalue (Show whather DF, RKB, Rf, GR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING OTHER: Drilling completed OTHER: Drilling completed 12 Describe Proposed or Completed Operations (Clearly state all peribent detail, and give peribent dute, including estimated date of staning any proposed work) SEE RULE 1103. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. H=40, ST&C conductor w/80 sks class G w/3% Cacl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-5: ST&C casing w/170.sks class G w/2% Cacl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment.		ouston, Tx 77252		Wildcat	•	
Serilos I Townchip 29N Range 18E NNOPM Colfax County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 7992 GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK		.9 Feet From The North	Tine and 2	8 Feet From Th	West	Tina
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 7992 GR 7	_ `					
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK	Section 1		41126	NMPM Colfa	X 77777777777777	County
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENT JOB COM		///////				
PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. TOTHER: Drilling completed 12 Describe Proceed or Completed Operations (Clearly state all perinent details, and give perinent dates, including estimated date of staning any proposed worl) SEE RULE 1103. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. H-40, ST&C conductor w/80 sks class G w/3% CaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-55 ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Thereby certify that the information through the best of my browkedge and boild. SIGNATURE DATE THE OPERATOR AND THE OPERATOR	11. Check	Appropriate Box to Indicate		-		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB X CASING TEST AND CEMENT JOB X OTHER: Drilling completed 12. Describe Proposed or Completed Operations (Clearly state all persistent datas), and give persistent datas, including estimated data of starting any proposed work) SEE RULE 1101. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. H-40, ST&C conductor w/80 sks class G w/3% CaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-55 ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Thereby certify that he informative should be best of my knowledge and boild. SHONARDER MADE THE PLANE SO 5-376-28 (This space for State Use) DISTIBLE OF STATE CASING THE PLANE SO 5-376-28	NOTICE OF IN	TENTION TO:	SUE	SEQUENT RE	PORT OF:	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB X COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB X CASING TEST AND CEMENT JOB X OTHER: Drilling completed 12 Describe Proceed or Completed Operations (Clearly state all perinent data), and give perinent data, including entimated date of staning any proposed work) SEE RULE 1103. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. H-40, ST&C conductor w/80 sks class C w/3% CaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-55 ST&C casing w/170.sks class C w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Thereby certify that he information about in your put profession data best of my thorwholes and boiled. SHANARING Department of State Use Thereby certify that he information about in your put profession data best of my thorwholes and boiled. SHANARING Department of State Use Thereby certify that he information about in your put profession data best of my thorwholes and boiled. SHANARING Department of State Use Thereby certify that he information about in your put profession and your put	PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	☐ AL	TERING CASING	
CASING TEST AND CEMENT JOB TOTHER: OTHER: Drilling completed OTHER: Drilling completed OTHER: Drilling completed OTHER: Drilling completed [12 Describe Proposed or Completed Operations (Clearly state all pertinent datalls, and give pertinent datas, including estimated data of starting any proposed 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. H-40, ST&C conductor w/80 sks class G w/3% CaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-55 ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Thereby cartly that has informative about the present of my knowledge and belief. SIGNATURE Department NAME L. D. Williamson THE DEPARTMENT STATE OF THE PROPERTY STATE OF THE P	TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	 (ਦ)	•	uent [
OTHER: Drilling completed 12 Describe Proposed or Completed Operations (Clearly state all perinent details, and give perinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb. H-40, ST&C conductor w/80 sks class G w/3% CaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-55 ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. I hereby cartly that the informatica about the part of the best of my knowledge and belief. SHONATURE L. D. Williamson THEPTICAL TO STATE OF THE PROPERTY NAMES L. D. Williamson THEPTICAL TO STATE OF THE PROPERTY NAMES AND TH	PULL OR ALTER CASING		1		OG YILD Y'DYILDON	INCH!
12 Describs Proposed or Completed Operations (Clearly state all perituent details, and give perituent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6/10/89 Spud. Drill 14 3/4" hole to 41'. Set and cement 2 jts (41') 11 3/4", 42 lb H-40, ST&C conductor w/80 sks class G w/3% CaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-55 ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. I hereby certly that the information should be best of my knowledge and belief. BIONATURE TITLE OPERATY NAME L. D. Williamson TILEPHONE NO.505-376-28	OTHER:	П	١		ed	نا
H-40, ST&C conductor w/80 sks class G w/3% CaCl. 6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 lb. J-55 ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. I hereby servily that the information about the best of my knowledge and belief. SIGNATURE L. D. Williamson THEEPHONE NO. 505-376-28 This space for State Use) DISTIPICT CLUSS AND TO THE TELEPHONE NO. 505-376-28	12. Describe Proposed or Completed Oper work) SEE RULE 1103.	rations (Clearly state all persinent details, a	<u> </u>			
6/11/89 Drill 11" hole to 333'. Set and cement 12 jts (327.75') 8 5/8", 24 1b. J-55 ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. SIGNATURE Describy that the information should be best of my knowledge and belief. SIGNATURE Describy that the information should be best of my knowledge and belief. SIGNATURE Describe the best of my knowledge and belief. SIGNATURE Describe the best of my knowledge and belief. SIGNATURE L. D. Williamson Telephone mo505-376-28) 11 3/4", 4	2 1b.
ST&C casing w/170 sks class G w/2% CaCl @ 15.8 ppg. Bumped plug w/500 psi. Cement to surface. 8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. I hereby certify that the information about the best of my knowledge and belief. SIGNATURE DOPERATIONAL L. D. Williamson TITLE Operations Superintendent DATE TYPE OR PRINTY NAMES L. D. Williamson TELEPHONE NO 505-376-28	6/11/89 Drill 11	.w conductor w/ou sks ." hole to 333'. Set an	class G W/3% Ca d cement 12 its	(327.75') 8	5/8", 24 1b.	J-55
8/21/89 Test casing & BOP w/600 psi for 30 mins. No pressure drop. 8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Thereby certify that the information aboving true and possible to the best of my knowledge and belief. SIGNATURE	ST&C cas	sing w/1700sks class G	w/2% CaCl @ 15.	8 ppg. Bumped	plug w/500	psi.
8/29/89 Drill 7 7/8" hole to 2588'. Logging. 8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Thereby certify that the information about the true and possible to the best of my knowledge and belief. SIGNATURE OPERATION NAMES L. D. Williamson THE OPERATION NAMES L. D. Williamson THE OPERATION NAMES TYPE OR FRINT NAMES L. D. Williamson THE OPERATION NAMES THE OPERATION NAMES THE OPERATION NAMES THE OPERATION NAMES THE OPERAT			20 N	1		
8/30/89 Set and cement 96 jts (2546') 5 1/2", 17 lb. J-55, LT&C casing w/675 sks silicalite @ 11 ppg. Plug down w/1000 psi. Waiting on completion equipment. Thereby certify that the information shows the best of my knowledge and belief. SIGNATURE Department Time Operations Superintendent DATE TYPE OR PRINT NAME L. D. Williamson TELEPHONE NO. 505-376-28				ressure drop.		
Thereby certify that the information about the period of the best of my knowledge and belief. SIGNATURE DEPTHONE NO. 505-376-28 (This space for State Use)	8/30/89 Set and	cement 96 jts (2546')	5 1/2", 17 1b.			
SIGNATURE TO THE Operations Superintendent DATE 9/6/89 TYPE OR PRINT NAME L. D. Williamson TELEPHONE NO. 05-376-28 (This space for State Use)	silicali	te @ 11 ppg. Plug down	w/1000 psi. Wa	iting on comp	letion equip	ment.
TYPE OR FRIDIT NAME L. D. Williamson TELEPHONE NO. 05-376-28 One of State Use DISTRICT STATE DISTRICT STATE Operations Superintendent DISTRICT STATE D						
TYPE OR FRIDIT NAME L. D. Williamson TELEPHONE NO. 05-376-28 One of State Use DISTRICT STATE DISTRICT STATE Operations Superintendent DISTRICT STATE D						
TYPE OR FRIDIT NAME L. D. Williamson TELEPHONE NO. 05-376-28 One of State Use DISTRICT STATE DISTRICT STATE Operations Superintendent DISTRICT STATE D	·	•				
TYPE OR PRINT NAME L. D. Williamson TELEPHONE NO. 05-376-28	I hereby certify that the information about is brus	e and complete to the best of my knowledge and	belia.			·
(This space for State Use) DISTRICT STATES OF THE PHONE NO. 05-376-28	SIGNATURE A PARTIE	Ellumaun	Operations Sup	erintendent	9/6/89	_
(This space for State Use)	TYPE OR FRONT NAME L. D.	Williamson			TELEPHONE NO 505-3	76-281
Ja Elekann DISTRICT SUPPLIES QUE DE	(This space for State Use)					
APPROVED BY 17 C 7 C 7 C 7 C 7 C 7 C 7 C 7 C 7 C 7	APPROVED BY SUTE SOFT	more	DISTRICT S	Playson	9-8-	x G

- TITLE -