

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-007-20101

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☐

OTHER Coal Methane

2. Name of Operator

Pennzoil Exploration and Production Company

3. Address of Operator

P.O. Box 2967, Houston, TX 77252

4. Well Location

Unit Letter D : 1022 Feet From The North Line and 792 Feet From The West Line

Section 11 Township 29N Range 18E NMPM Colfax County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7924 GR

7. Lease Name or Unit Agreement Name

Cerroso Canyon  
2918

8. Well No.

111-D

9. Pool name or Wildcat

Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Drilling completed ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-22-89 Spud.

7-23-89 Drill 11" hole to 350'. Set and cement 13 jts (336') 8 5/8", 24 lb. J-55, ST&C casing w/220 sks class G w/2% CaCl and 1/4 lb/sk Flocele. Float did not hold. Shut in under pressure.

7-24-89 WOC 27 hours, test casing and BOP w/600 psi for 30 minutes. No pressure drop.

7-31-89 Drill 7 7/8" hole to 2525'.

8-01-89 Set and cement 105 jts (2505.3') 5 1/2", 17 lb. J-55, LT&C casing w/550 sks silicalite @ 11.0 ppg. Bumped plug w/1000 psi. Cement to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE Operations Superintendent DATE 8-8-89

TYPE OR PRINT NAME L. D. Williamson

TELEPHONE NO. 505-37602817

(This space for State Use)

APPROVED BY R. E. Johnson DISTRICT SUPERVISOR DATE 8-9-89

CONDITIONS OF APPROVAL, IF ANY: