Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office Revised March 25, 1999 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 District II 30-007-20103 OIL CONSERVATION DIVISION 811 South First, Artesia, NM 87210 5. Indicate Type of Lease District III 2040 South Pacheco STATE \square 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV State Oil & Gas Lease No. 2040 South Pacheco, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH VPR 'A' PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other COALBED METHANE Name of Operator 8. Well No. EL PASO ENERGY RATON, L.L.C. Address of Operator 9. Pool name or Wildcat P.O. BOX 190; RATON, NM 87740 Well Location Unit Letter A: 660' feet from the NORTH line and 990' feet from the EAST line Section 34 Township 32N Range 19E NMPM COLFAX County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8058' (GR) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ALTERING CASING ☐ CHANGE PLANS **TEMPORARILY ABANDON** COMMENCE DRILLING OPNS. **PLUG AND ABANDONMENT** PULL OR ALTER CASING MULTIPLE CASING TEST AND COMPLETION **CEMENT JOB** OTHER: OTHER: RE-ENTRY & COMPLETION 12. 1/14-15/00 Drill out cement plugs. Clean out to 2420' Perforate 1490'-1491'. Cement squeezed with 131 sxs. Ran CBL. 3/27-30/00 Perforate 600'-601'& 1120'-1121'. Cement sqzd with 42 sxs via tubing & 52 sxs via casing. Clean out to 2420' 5/09-22/00 Perforate 910'-911'. Cement sqzd with 50 sxs. Repeated cement squeeze with 50 sxs. Ran CBL 1500'-surface. Clean out to 2410 Perforate: 2332' - 2334' & 2316' - 2318'. All 4 spf. 5/28/00 Perforate: 2307' – 2311', 2266' – 2270', 2212' – 2218'. All 4spf. 6/11/00 Stimulate: 30000# 20/40 & 90000# 12/20 Sand with 680000 scf N2 70 Quality foam. 6/13/00 Perforate: 1354' - 1358', 1281' - 1285', 1272' - 1276'. All 4spf. 6/14/00 Stimulate: 20000# 20/40 & 50000# 12/20 Sand with 220000 scf N2 70 Quality foam. 6/15/00 6/16/00 Perforate: 1197'-1201', 1154'-1158', 1097'-1101', 1060'-1068', 974'-979', 936'-942', & 930'-932', All 4 spf. Stimulate: 40000# 20/40 & 155000# 12/20 Sand with 1025000 scf N2 70 Quality foam. Perforate: 722'-726', 693'-697', 659'-663'. All 4spf. 6/25/00 Stimulate: 20000# 20/40 & 80000# 12/20 Sand with 545000 scf N2 70 Quality foam. 6/27/00 Clean out to 2410°. Ran tubing & rods. Well ready for production. 7/11-13/00 I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE WELL SITE SUPERVISOR DATE 09/01/00 Type or print name: Telephone No.: (505) 445-4620 (This space for State use) TITLE DISTRICT SUPERVISOR DATE 8/6/00

APPPROVED BY

Conditions of approval, if ar