

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO. **30-007-20108**

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR D

8. Well No. **20**

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190; RATON, NM 87740

4. Well Location

Unit Letter N : 742' feet from the SOUTH line and 1752' feet from the WEST line

Section 32 Township 31N Range 18E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

8617' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: **RE-ENTER & COMPLETE** ☒

12.

1/22-28/00 Drill out cement plug 0'-250', CIBP and cement 1570'-1688', & cement and CIBP 1820'-1844'. Clean out to 2125'.

2/19/00 Perforate: 1976'-1982', 1937'-1941', 1912'-1916'. All 4spf.

2/22/00 Stimulate: 25000# 20/40 & 100000# 12/20 Sand. 500000 scf N2 70 Quality foam.

2/24/00 Perforate: 1884'-1888', 1873'-1877', 1849'-1853', 1805'-1809', 1783'-1793', 1695'-1702'. All 4spf.

2/25/00 Stimulate: Interval 1789'-1888' with 25000# 20/40 & 50000# 12/20 Sand. 365000 scf N2 70 Quality foam.

2/28/00 Stimulate: Interval 1695'-1702' with 25000# 20/40 & 100000 # 12/20 Sand. 515000 scf N2 70 Quality foam.

3/05-09/00 Clean out to 2111'. Ran After frac Log (Patterson). Ran tubing & rods. Well ready to produce.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Joel L. Pettit TITLE WELL SITE SUPERVISOR DATE 08/17/00

Type or print name: **JOEL L. PETTIT** Telephone No.: (505) 445-4620

(This space for State use)

APPROVED BY Ry E. Johnson TITLE **DISTRICT SUPERVISOR** DATE 8/25/00

Conditions of approval, if any: