

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20114
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: VPR 'A'
8. Well No. 04
9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☐ Other COALBED METHANE

2. Name of Operator
SONAT RATON, LLC

3. Address of Operator
P.O. BOX 190; RATON, NM 87740

4. Well Location
Unit Letter K : 1631' feet from the SOUTH line and 1539' feet from the WEST line
Section 31 Township 32N Range 20E NMPM COFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8085' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: RESTORATION ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08/10/99 MIRU Leed Energy Service rig. TIH w/ tubing. Halliburton spotted 35 sk cement plug 1690'-1515' and a 50 sk plug from 909'-659'. WOC.

08/11/99 Tagged cement plug w/ tubing at 820'. Halliburton spotted a 35 sk cement plug from 407'-232'. (8 5/8" shoe at 351'.) Halliburton spotted a 10 sk surface plug from 30'-0'. Rigged down and moved

****ROY JOHNSON GAVE VERBAL PERMISSION TO P&A.****

Dry hole marker was installed.

No restoration was required since the well was re-drilled as the VPR 'A' 04X (30-007-20135) on the same pad.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE SR. PETROLEUM ENGINEER DATE 10/04/99

Type or print name: DON LANKFORD

Telephone No.: (505) 445-4621

(This space for State use)

APPROVED BY Ry Johnson TITLE DISTRICT SUPERVISOR DATE 10/14/99

Conditions of approval, if any: