

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-007-20116
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other Coalbed Methane <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator SONAT RATON, L.L.C.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 190; Raton, NM 87740		7. Lease Name or Unit Agreement Name:
4. Well Location Unit Letter B 1074 feet from the North line and 2276 East Line. Section 1 Township 31 N Range 19 E NMPM Colfax County		8. Well No. VPR 'A' 7
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8272'(GR)		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

*Unitel Doly*

7/1/99: RU ~~Thorton~~ Rig 9. Spud well at 5 am.

7/2/99: Drill 17 1/2" hole to 356'

7/3/99: Ran and set 13 3/8" 48# H-40 surface casing at 350'  
Cement with 300 sx. Cement. Circ. 32 sx. to surface.

7/6/99: Drill 12 1/4" hole to 2662'. Ran open hole logs.  
Ran and set 9 5/8" 36# J-55 surface casing at 2662'  
Cement with 525 sx. No circ. To surface.

7/8/99: Pumped Bradenhead squeeze with 300 sx. Cement to surface.

7/15/99: Drilled 8 3/4" hole to 6416'. Ran open hole logs DIL/Caliper/GR.

7/19/99: Conditioning hole to run 7" casing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE Sr. Petroleum Engineer

DATE 7/21/99

Type or print name Donald R. Lankford

Telephone No. (505) 445-4620

This space for State Use

APPROVED BY Ry E. Johnson TITLE DISTRICT SUPERVISOR DATE 7/22/99

Conditions of approval, if any