

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-007-20125

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:
VPR 'A'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other Coalbed Methane

2. Name of Operator

SONAT RATON, L.L.C.

3. Address of Operator

P.O. Box 190; Raton, NM 87740

8. Well No. - **11**

9. Pool name or Wildcat

4. Well Location

Unit Letter H : 1596.80 feet from the North line and 1226.41 feet from the East line

Section 02
County

Township 31 N

Range 19 E

NMPM Colfax

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8322'(GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☒ COMPLETION

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Perforated casing 1271 - 1475 W/4 SPF
Frac'd 1471 - 1475 W/ 52,000 lbs of sand.
Set RBP @ 1450'.
Perforated casing 1426' - 1430' W/4 SPF.
Frac'd 1426 - 1430 with 52,000 lbs of sand.
Set RBF at 1250'
Perforated casing 1203 - 1209 W/4 SPF.
Frac'd 1203 - 1209 with 34,000 lbs of sand.
Clean out to 1700'
Run production equipment (PC Pump).
B.J. Services mixed & pumped 30 sks PLHS plus additives down the annulus.
Shut down with 80 psi on the casing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Donald R. Lankford TITLE Sr. Petroleum Engineer DATE 09/30/99

Type or print name Donald R. Lankford Telephone No. (505) 445-4621

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 9/30/99

Conditions of approval, if any: