

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO.  
30-007-20127

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:  
**VPR 'A'**

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other Coalbed Methane

2. Name of Operator

**SONAT RATON, L.L.C.**

8. Well No. - **13**

3. Address of Operator

P.O. Box 190; Raton, NM 87740

9. Pool name or Wildcat

4. Well Location

Unit Letter J : 1759.98 feet from the South line and 1950.88 feet from the East line

Section 35  
County

Township 32 N

Range 19 E

NMPM Colfax

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
8281'(GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☒ COMPLETION

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Perforated casing 2329 - 2333 W/4 SPF.

Frac'd 2329 - 2333 W/27,100 lbs of sand.

Set RBP at 2260'

Perforated casing 2240 - 2244, 2210 - 2214 W/4 SPF.

Frac'd 2210 - 2244 W/79, 100 lbs. of sand.

Set RBP at 1550. Shot 8 squeeze holes 1400' - 1402'

HES mixed & pumped 350 sks midcon 2 plus additives.

Circulated 50 bbls of slurry to the pit.

Drilled cement from 1328 to 1420'. Test casing to 500 PSI. Held ok.

Clean out to 2564'

Run production equipment (PC Pump).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Donald R. Lankford TITLE Sr. Petroleum Engineer DATE 09/30/99

Type or print name Donald R. Lankford Telephone No \_\_\_\_\_

(This space for State use)

APPROVED BY Ry E. Johnson TITLE **DISTRICT SUPERVISOR** DATE 9/30/99

Conditions of approval, if any: