

180514 Submit 3 Copies To Appropriate
District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1006 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-007-20142

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR A

8. Well No. 33

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other Coalbed Methane

2. Name of Operator

Sonat Raton, L.L.C.

3. Address of Operator

P.O. Box 190, Raton, NM 87740

4. Well Location

Unit E : 1573' feet from the North line and 1198' feet from the WEST line

Section 35

Township 32N

Range 19E

NMPM COLFAX

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8262' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

02/01/00: Spud @ 12:00 Noon Drill 11" surface hole to 350'. Run 16 jts. 8-5/8 to 330' cement with 100 sx. of midcon plus + Additives. WOC

02/02/00: WOC. Drill 7-7/8" hole to 2340'.

02/03/00: Drill to 2480'. Reeves ran open hole logs.
Run 5 1/2" casing. Set and cement at 2441'.
Cemented with 310 sacks of Midcon 2 plus additives.
No cement circulated to surface.

02/11/00: MIRU Patterson Wireline. TOC = 274'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE Sr. Petroleum Engineer DATE 02/16/00

Type or print name Donald R. Lankford

Telephone No. (505)445-4621

(This space for State use)

APPROVED BY Ry E Johnson TITLE DISTRICT SUPERVISOR DATE 2/23/00

Conditions of approval, if any: