Office	State of I				Form C-103
<u>District I</u>	Energy, Minerals and Natural Resources				Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240				WELL API NO.	30-007-20149
District II 811 South First, Artesia, NM 87210	ortesia NM 87210 OIL CONSERVATION DIVISION			5 I I' . T	CI
District III	2040 South Pacheco			5. Indicate Type	
00 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505			STATE		
2040 South Pacheco, Santa Fe, NM 87505			6. State Oil & 0	Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A				7. Lease Name o	or Unit Agreement Name:
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH					TYPE W
PROPOSALS.)					VPR D
1. Type of Well: Oil Well □ Gas Well ■ Other					
Oil Well Gas Well  2. Name of Operator	Other				10
SONAT RATON, LLC				8. Well No.	19
3. Address of Operator			9. Pool name or	Wildcat	
P.O. BOX 190; RATON, NM 87740				Traduction of the second of th	
4. Well Location					
Unit Letter1:165'	7' feet from theSou	ıth line	and1307'f	feet from theEast	tline
Section 31 Township		18E		LFAX Cour	nty
10	0. Elevation (Show w			c.)	
		8689' (			
	ropriate Box to Ind	licate Na		-	
NOTICE OF INTE				SEQUENT RE	
PERFORM REMEDIAL WORK   PI	LUG AND ABANDON		REMEDIAL WOR	к Ц	ALTERING CASING $\Box$
TEMPORARILY ABANDON   C	HANGE PLANS		COMMENCE DRI	LLING OPNS.	PLUG AND
PULL OR ALTER CASING	ULTIPLE		CASING TEST AN	۸D [_	ABANDONMENT
	OMPLETION	L/	CEMENT JOB		
OTHER					
OTHER:			OTHER:		
12.					
4/1/00 Spud well at 8:00 PM	1 Drill 11" hole to 180	)' Run 8-5	5/8" casing to 3 (2)	RI numned 125 cs	v Type III ± 20% CaCl2 2
4/1/00 Spud well at 8:00 PM. Drill 11" hole to 180'. Run 8-5/8" casing to 3.32'. BJ pumped 125 sx Type III + 2% CaCl2. 3 bbls cement returned to surface. WOC 8 hrs. Drill 7-7/8" hole.					
			, 0 110101		
		335'. BJ j	pumped 125 sx Ty	pe III + 2% CaCl2.	16 bbls cement returned
to surface. WOC 8 hr	s. Drill 7-7/8" hole.				
4/2/00 Daill 7.7/92 hala to 2/	0002 DIID	1 10061	. 2251 D. 6 1/0		
Drill 7-7/8" hole to 2000'. RU Reeves and log 1886' to 335'. Run 5-1/2" casing to 1970'. Cement with BJ. Mix and Pump 200 sx of cement. 18 bbls cement to surface. Release rig					
Tump 200 SX of come	int. To bols cement to	surface. R	crease rig		
I hereby certify that the information about	ove is true and comple	te to the b	est of my knowled	ge and belief.	
SIGNATURE BR Lanca	/ TITLE	CD DET		MEED DATE	4/11/00
SIGNATURE	IIILE_	SK. PE	ROLEUM EN JI	NEEKDATE	4/11/00
Type or print name: DON LANKFORD Telephone No.: (505) 445-4621					
(This space for State use)	$\bigcap$				
APPPROVED BY Ty Electron TITLE DISTRICT SUPERVISOR DATE 4/12/00					
Conditions of approval, if any:					