

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-007-20160
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator SONAT RATON, LLC		6. State Oil & Gas Lease No.
3. Address of Operator P.O. BOX 190; RATON, NM 87740		7. Lease Name or Unit Agreement Name: VPR B
4. Well Location Unit Letter <u>A</u> : <u>368</u> feet from the <u>North</u> line and <u>1038</u> feet from the <u>East</u> line Section <u>26</u> Township <u>30N</u> Range <u>18E</u> NMPM COLFAX County		8. Well No. 24
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8101' (GR)		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12.

4/10/00 Spud well at 3:30 AM. Drill 11" hole to 350'. Run 8-5/8" casing to 335. BJ Pumped 110 sx Type III + Adds. Cement to surface. WOC 13 hrs. Cement would not support Casing. Re-cement with 75 sx. Staged cement into place. WOC 1.5 hrs.

4/11/00 WOC 9 hrs. Drill 7-7/8" hole.

4/12/00 Drill to TD of 2400'. RU Patterson and log 2385' to 335'. Run 5-1/2" casing to 2374'. Cement with BJ. Mix and Pump 250 sx of cement. 20 bbls cement to surface. Release rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE SR. PETROLEUM ENGINEER DATE 4/22/00

Type or print name: DON LANKFORD Telephone No.: (505) 445-4621

(This space for State use)

APPROVED BY R. E. Johnson TITLE **DISTRICT SUPERVISOR** DATE 5/10/00
Conditions of approval, if any: