

180514 Submit 3 Copies To Appropriate
District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-007-20168

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR A

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other Coalbed Methane

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. Box 190, Raton, NM 87740

8. Well No. 39

9. Pool name or Wildcat

4. Well Location

Unit N : 685 feet from the South line and 1779' feet from the West line

Section 20

Township 32N

Range 20E

NMPM COLFAX

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8041' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

02/15/01: RU Leede CU. TIH with EZSV cement retainer on 2 7/8" tbg and set at 1752'. Circulate hole above retainer with 9 ppg mud. Pump 51 sks Midcon II at 14 ppg with 5#/sk Gilsonite, 6% salt and 0.3% Versaset filling the hole volume + 10% below retainer with a 50' cmt cap on top of retainer. RU Patterson Wireline. Ran freepoint showing 5 1/2" casing free at 172'. Perforate csg with 4 holes at 438'. Established circulation through perfs. TIH with 2 7/8" tbg open ended to 812'. Pump 28 sks Midcon II at 14 ppg w/same additives spotting a balanced cmt plug from 812'-450'. TOH w/ tbg. Pump cmt down 5 1/2" csg through perfs @ 438' and back to surface with 96 sks Midcon II at 14 ppg with same additives. Shut well in.
Top plug: Surface to 438'
2nd plug: 450'-812'
Cement Retainer: 1752'
Bottom Plug: 1702'-2272'

02/18/01: Cut off 8 5/8" casing 2' below ground level. Weld on cap. Weld P&A pole 4"x4' on cap with inscription as follows: "El Paso, VPRA 39, 685' FSL, 1779' FWL, 'N' Sec 20-T32N-R20E". Well P&A'd 02/17/01.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Ordemann TITLE Engineer DATE 02/21/01

Type or print name William M. Ordemann

Telephone No. (505)445-6724

(This space for State use)

APPROVED BY R. E. Johnson TITLE DISTRICT SUPERVISOR DATE 2/23/2001

Conditions of approval, if any: