

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO. 30-007-20169
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: VPR A
8. Well No. 40
9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other COALBED METHANE	
2. Name of Operator EL PASO ENERGY RATON, L.L.C.	
3. Address of Operator P.O. Box 190, Raton, NM 87740	
4. Well Location Unit Letter _____ O : 1227 feet from the South line and 1360 feet from the East line Section 20 Township 32N Range 20E NMPM Colfax County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8060' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: COMPLETION ☒

12.  
2/24/00 Ran CBL (Patterson). TOC 1970'.  
2/25/00 Perforate 1945'-1946'. Cement squeezed with 215 sxs. Did not circulate.  
3/13/00 Ran CBL from 1680'. Found no cement above 1680'.  
6/01/00 Drill cement 1685'-1965'. Would not test. Inject 1.5 bpm @ 1000#.  
6/02/00 Cement sqzd 50 sxs. Tested squeeze 500# for 3 hours. Ran CBL (Patterson). No cement above 1800'.  
Perforate 1781'-1782'. Cement squeezed with 50 sxs.  
6/03/00 Ran CBL (Patterson). Tagged @ 1528', TOC @ 1460'. Perforate 1410'-1411'. Cement squeezed with 50 sxs.  
6/04/00 Ran CBL (Patterson). Tagged @ 1255', TOC 1090'. Perforate 1080'-1081'. Cement sqzd with 50 sxs.  
6/05/00 Ran CBL (Patterson). Tagged @ 930', no cement behind casing there.  
Drill 930'-1116', 1275'-1432', 1560'-1809', 1820'-1967'. Clean out to 2250'.  
Ran CBL (Patterson) TOC 940'.  
6/06/00 Perforate 1890'-1891' & 1790'-1791'. Set retainer @ 1850'. Cement sqzd 40 sxs via tubing & 40 sxs via casing.  
6/07/00 Drill cement & retainer & clean out to 2280'. Tested to 1500#.  
6/09/00 Perforate: 2244'-2248', 2236'-2240', 2221'-2225', 2201'-2205', 2173'-2177', 2157'-2161'. All 4 spf.  
6/10/00 Stimulate: 20000# 20/40 & 100000# 12/20 sand with 76647 gals 20# Delta 140/Sandwedge.  
Perforate: 2062' - 2066' & 2045' - 2049'. All 4 spf.  
6/11/00 Stimulate: 10000# 20/40 & 40000# 12/20 sand with 30351 gals 20# Delta 140/Sandwedge. Perforate: 1791' - 1799' (4 spf).  
Stimulate: 10000# 20/40 & 30000# 12/20 sand with 25397 gals 20# Delta 140/Sandwedge.  
6/12-14/00 Clean out to 2327'. Ran After frac Log (Patterson). Perforate 800'-801'. Cement sqzd with 110sxs. Circ. Cement to surface.  
6/15-16/00 Clean out well. Tested sqz to 1100 psi - OK. Ran tubing & rods. Well ready for production.

325  
215  
50  
50  
50  
50

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Joel L. Pettit TITLE WELL SITE SUPERVISOR DATE 08/28/00  
Type or print name JOEL L. PETTIT Telephone No. (505) 445-4620  
(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 8/30/00  
Conditions of approval, if any: