

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-007-20179
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator SONAT RATON, LLC		6. State Oil & Gas Lease No.
3. Address of Operator P.O. BOX 190; RATON, NM 87740		7. Lease Name or Unit Agreement Name: VPR D
4. Well Location Unit Letter <u>A</u> : <u>1037'</u> feet from the <u>North</u> line and <u>1169'</u> feet from the <u>East</u> line Section <u>1</u> Township <u>30N</u> Range <u>17E</u> NMPM COFAX County		8. Well No. 13
10. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>8373' (GR)</u>		9. Pool name or Wildcat
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPLETION <input type="checkbox"/> OTHER: <input type="checkbox"/>		SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>

12.

4/6/00 Spud well at 5:30 AM. Drill 11" hole to 350'. Run 8-5/8" casing to 334'. BJ pumped 125 sx Type III + 2% CaCl₂. 3 bbls cement returned to surface. WOC 8 hrs. Drill 7-7/8" hole.

4/7/00 Drill to 1830'. RU Patterson and log 1733' to 330'. Run 5-1/2" casing to 1818'. Cement with BJ. Mix and Pump 140 sx of cement. Had to cut cement because hole packed off. No cement to surface. Release rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE SR. PETROLEUM ENGINEER DATE 4/11/00

Type or print name: DON LANKFORD Telephone No.: (505) 445-4621

(This space for State use)

APPROVED BY Ry E Johnson TITLE DISTRICT SUPERVISOR DATE 4/12/00
Conditions of approval, if any: