Office	State of New Mexico				Form C-103			
District I 1625 N. French Dr. J	District I Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 87240					Revised March 25, 1999 WELL API NO. 30-007-20180		
District II	District []					. 30-007-20180		
811 South First, Artesia, NM 87210 OIL CONSERVATION DIVISION District III 2040 South People on					5. Indicate Type	e of Lease		
1000 Rio Brazos Rd. Aziec NM 87410					STATE			
District IV Santa Fe, NM 87505 2040 South Pacheco, Santa Fe, NM 87505						Gas Lease No.		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A					7. Lease Name or Unit Agreement Name:			
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH								
PROPOSALS.) 1. Type of Well:						VPR D		
Oil Well Gas Well Other								
2. Name of Operator					8. Well No.	14		
SONAT RATON, LLC					o. Well No.	14		
3. Address of Operator					9. Pool name or Wildcat			
P.O. BOX 190; RATON, NM 87740 4. Well Location								
4. Well Locatio	n							
Unit Lett	ter F	1458'feet from the	North	line and 195	(1) foot from the	117		
			1101111		leet from the	Westline		
Section	6 Towns	ship 30N Range	18E	NMPM CO	FAX Cour	nty		
10. Elevation (Show whether DR, RKB, RT, GR, etc.)								
8532' (GR)								
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data								
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK					SEQUENT RE			
TENTONININE	-DIAL WORK	FLOG AND ABANDO	۷ Ц	REMEDIAL WOR	к 📙	ALTERING CASIN	G 🗀	
TEMPORARILY ABANDON				COMMENCE DRI	ILLING OPNS. PLUG AND ABANDONMENT			
PULL OR ALTER CASING MULTIPLE			 1					
PULL OR ALTER CASING				1	CASING TEST AND CEMENT JOB			
				OLINENT JOB				
OTHER:				OTHER:				
12.								
3/5/00	Spud well at 5:00) PM. Drill 40' of 11" Su	rface hole.	. Rig broke down. W	Vait on rig renairs			
3/5/00 Spud well at 5:00 PM. Drill 40' of 11" Surface hole. Rig broke down. Wait on rig repairs.								
Resume work at noon. Drill of 11" Surface hole. Run 8-5/8" Casing to 334'. Cement with Halliburton. Pump 100 st Midcon 2 + adds. 9 bbls cement to surface WOC 8 hrs. Drill 7-7/8" hole to TD @ 2060'.								
	Midcon 2 + adds.	. 9 dois cement to surface	; WOC 8 h	ors. Drill 7-7/8" hole	e to TD @ 2060'.			
3/9/00	WOC 8 hrs. Drill 7-7/8" hole to TD @ 2020'.							
2/10/00								
3/10/00 Log Wellbore. Run 5-1/2" casing to 2001'. Mix and Pump300 sx. Midcon2 + adds. 20 BBLS cement to surface.								
71 1 10 10 1								
I hereby certify the	at the information	n above is true and compl	lete to the l	best of my knowled	ge and belief.			
SIGNATURE	DR Land	1 TITLE	SR PF	TROLEUM ENGIN	JEER DATE	3/25/00		
					VEEKDATE	3/23/00		
		ORD Telephone No.: (50	J5) 445-46	21				
(This space for Sta	ite use)	1				_	-	
APPPROVED BY TITLE DISTRICT SUPERVISOR DATE 4/4/00								
Conditions of approval, if any:								
	•							