

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-105
Revised March 25, 1999

WELL API NO.	30-007-201856
5. Indicate Type of Lease STATE ☐ FEE ☒	
State Oil & Gas Lease No.	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER X Coal Bed Methane		7. Lease Name or Unit Agreement Name VPR 'B'	
b. Type of Completion: NEW WORK PLUG DIFF. RESVR OTHER X WELL ☒ OVER ☐ DEEPEN ☐ BACK ☐ ☐ ☐ ☐		8. Well No. 06	
2. Name of Operator EL PASO ENERGY - RATON, L.L.C.		9. Pool name or Wildcat Van Bremmer Canyon - Vermejo Gas	
3. Address of Operator PO BOX 190, RATON, NEW MEXICO 87740			
4. Well Location Unit Letter N : 1101 Feet From The SOUTH Line and 1655 Feet From The WEST Line Section 36 Township 30N Range 18E NMPM COLFAX County			
10. Date Spudded 05/04/00	10. Date T.D. Reached 05/05/00	11. Date Compl. (Ready to Prod.) 07/30/00	12. Elevations (DF& R(B. RT, GR, etc.) 8094'
13. Elev. Casinghead 8094'			
15. Total Depth 2582'	16. Plug Back T.D. 2560'	17. If Multiple Compl. How Many Zones? 0	18. Intervals Drilled By 0 - TD
19. Producing Interval(s), of this completion - Top, Bottom, Name 2205' - 2445' Vermejo Coals			20. Was Directional Survey Made No
21. Type Electric and Other Logs Run Density Log, Induction Log, CBL			22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	332'	11"	100 sx.	None
5 1/2"	17#	2570'	7 7/8"	375 sx.	
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
25. TUBING RECORD					
SIZE	DEPTH SET	PACKER SET			
2 7/8"	2456'	N/A			
26. Perforation record (interval, size, and number) 2205' - 2209', 2249' - 2253', 2265' - 2269', 2299' - 2306', 2342' - 2346' (4 SPF) 2403' - 2410', 2425' - 2429', 2441' - 2445' (All 4SPF) Vermejo Coals					
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
2205' - 2445'		50,000# 20/40 sand			
		150,000# 12/20 sand			

28. PRODUCTION							
Date First Production 10/15/00		Production Method (Flowing, gas lift, pumping - Size and type pump) 30-N-095 pc pump			Well Status (Prod. or Shut-in) Prod.		
Date of Test 09/20/00	Hours Tested 24 Hours	Choke Size Full 2"	Prod'n For Test Period N/A	Oil - Bbl N/A	Gas - MCF 145	Water - Bbl. 90	Gas - Oil Ratio N/A
Flow Tubing Press. 0	Casing Pressure 5 psi	Calculated 24-Hour Rate	Oil - Bbl. N/A	Gas - MCF 145	Water - Bbl. 90	Oil Gravity - API - (Corr.) N/A	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel						Test Witnessed By: Larry Casey	
30. List Attachments							

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief			
Signature	Printed Name	Title	Date
Ruth Luksich	Ruth Luksich	Sr. Field Administrative Spec.	10/24/00

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Ozite
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. Raton - surface - 74'
T. Blinbry	T. Gr. Wash	T. Morrison	T. Vermejo - 2194' - 2500'
T. Tubb	T. Delaware Sand	T. Todillo	T. Trinidad 2500'
T. Drinkard	T. Bone Springs	T. Entrada	T. T.
T. Abo	T. T.	T. Wingate	T. T.
T. Wolfcamp	T. T.	T. Chinle	T. T.
T. Penn	T. T.	T. Permian	T. T.
T. Cisco (Bough C)	T. T.	T. Penn "A"	T. T.

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from
to
feet.

NO. 2, FROM
to

.....

LITHOLOGY RECORD

(Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
From	To	Thickness In Feet	Lithology