

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-105
Revised March 25, 1999

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

a. Type of Well: OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER Coal Bed Methane		7. Lease Name or Unit Agreement Name VPR 'B'
b. Type of Completion: NEW WORK PLUG BACK DIFF. RESVR. OTHER WELL ☒ OVER ☐ DEEPEN ☐		8. Well No. 07
2. Name of Operator EL PASO ENERGY - RATON, L.L.C.		9. Pool name or Wildcat Van Bremmer Canyon - Vermejo Gas
3. Address of Operator PO BOX 190, RATON, NEW MEXICO 87740		

4. Well Location Unit Letter O : 860 Feet From The SOUTH Line and 1706 Feet From The EAST Line Section 36 Township 30N Range 18E NMPM COLFAX County					
10. Date Spudded 05/06/00	10. Date T.D. Reached 05/07/00	11. Date Compl. (Ready to Prod.) 08/07/00	12. Elevations (DF& R(B. RT. GR. etc.) 8076'	13. Elev. Casinghead 8076'	
15. Total Depth 2570'	16. Plug Back T.D. 2511'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By 0 - TD	Rotary Tools None	Cable Tools None
19. Producing Interval(s), of this completion - Top, Bottom, Name 2178' - 2454' Vermejo Coals				20. Was Directional Survey Made No	
21. Type Electric and Other Logs Run Density Log, Induction Log, CBL				22. Was Well Cored No	

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24 #	327'	11"	100 sx.	None
5 1/2"	15.50#	2545'	7 7/8"	350 sx.	

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	2384'	N/A
26. Perforation record (interval, size, and number) 2178' - 2182', 2209' - 2209', 2216' - 2220'; (All 4SPF) 2390' - 2394', 2413' - 2420', 2425' - 2429', 2449' - 2454' (All 4SPF) Vermejo Coals				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 2178' - 2454' 50,000# 20/40 sand 120,000# 12/20 sand			

28. PRODUCTION							
Date First Production 10/15/00		Production Method (Flowing, gas lift, pumping - Size and type pump) 30-N-095 pc pump			Well Status (Prod. or Shut-in) Prod.		
Date of Test 09/20/00	Hours Tested 24 Hours	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 2	Water - Bbl. 250	Gas - Oil Ratio N/A
Flow Tubing Press. 0	Casing Pressure 5 psi	Calculated 24-Hour Rate	Oil - Bbl N/A	Gas - MCF 2	Water - Bbl. 250	Oil Gravity - API - (Corr.) N/A	
29. Disposition of Gas (Sold, used for fuel, vented, etc.)						Test Witnessed By	

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Printed Name Ruth Luksich	Title Sr. Field Administrative Spec./	Date: 10/24/00
------------------------------	--	----------------

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Canyon	T. Cisca (Bough C)
T. Strawn	T. Penn
T. Atoka	T. Wolfcamp
T. Miss	T. Abbo
T. Devonian	T. Drinkard
T. Silurian	T. Tubb
T. Montoya	T. Blinbry
T. Simpson	T. Paddock
T. McKee	T. Glorieta
T. Ellenburger	T. San Andres
T. Gr. Wash	T. Grayburg
T. Delaware Sand	T. Queen
T. Bone Springs	T. 7 Rivers
T.	T. Yates
T.	B. Salt
T.	T. Salt
T.	T. Anhy

T. Penn. "A"	T. Penn. "B"
T. Permian	T. Penn. "C"
T. Chinle	T. Penn. "D"
T. Wingate	T. Leadville
T. Entrada	T. Madison
T. Todilto	T. Elbert
T. Morrison	T. McCracken
T. Dakota	T. Ignacio Otzie
Base Greenhorn	T. Granite
T. Gallup	T. Raton - surface - 702
T. Mancos	T. Vermejo 2165' - 2468'
T. Point Lookout	T. Trinidad - 2468'
T. Menefee	
T. Cliff House	
T. Pictured Cliffs	
T. Kirtland-Fruitland	
T. Ojo Alamo	

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

LITHOLOGY RECORD

(Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet

Lithology