Submit 3 Copies To Appropriate State of New Mexico Form C-103 District Office Energy, Minerals and Natural Revised March 25, 1999 District I WELL API NO. 30-007-20193 1625 N. French Dr., Hobbs, NM Resources 87240 District II 5. Indicate Type of Lease 811 South First, Artesia, NM 87210 OIL CONSERVATION DIVISION STATE \Box FEE District III 2040 South Pacheco 1000 Rio Brazos Rd., Aztec, NM 6. State Oil & Gas Lease No. Santa Fe, NM 87505 87410 District IV 2040 South Pacheco, Santa Fe, NM SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK Name: TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) VPR D 1. Type of Well: Oil Well Gas Well Other COALBED METHANE Name of Operator 8. Well No. 6 EL PASO ENERGY RATON, L.L.C. 3. Address of Operator 9. Pool name or Wildcat P.O. BOX 190; RATON, NM 87740 Well Location Unit Letter E : 1346'_feet from the __North ___ line and __1204'__feet from the __West __ line Section 8 Township 30N Range 18E NMPM COLFAX County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8426' (GR) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON ☐ CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND **ABANDONMENT** PULL OR ALTER CASING ☐ MULTIPLE CASING TEST AND COMPLETION **CEMENT JOB** OTHER: OTHER: COMPLETION 12. 4/14/00 Ran CBL (Patterson). TOC 2057'. Perforate 2030'-2031' & 1870'-1871'. Cement squeezed with 250 sxs. 4/20/00 Ran CBL. Tag @ 1646'. TOC 120'. Clean out to 1910'. Pump in 2.5 bpm with 1000#. 6/21/00 6/22/00 Cement squeezed with 50 sxs. 6/27-29/00 Clean out to 2100'. Ran CBL (Patterson). TOC 150'. Perforate: 2078'-2081', 2064'-2067', 2042'-2045', 1973'-1975', 1947'-1950', 1913'-1916', 1909'-1911', 1879'-7/25/00 1882'. All 4 spf. 8/01/00 Stimulate: 23500# 20/40 & 105000# 12/20 Sand with 640000 scf N2 70 Quality foam. Perforate: 1820' – 1830', 1804' – 1814', All 4 spf. Stimulate: 20000# 20/40 & 67000# 12/20 Sand with 200000 scf N2 70 Quality foam. 8/05-26/00 Clean out to 2096'. Ran tubing & rods. Well ready for production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. feel L **SIGNATURE** TITLE WELL SITE SUPERVISOR DATE 09/04/00 Type or print name: JOEL L. PETTIT Telephone No.: (505) 445-4620 (This space for State use) APPPROVED TITLE DISTRICT SUPERVISOR DATE 9/6/00

Conditions of approval, if any: