

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-007-20204

5. Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER _____

7. Lease Name or Unit Agreement Name

VPR *A

b. Type of Completion:

NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER ☐

2. Name of Operator

8. Well No.

45

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190, RATON, NEW MEXICO 87740

9. Pool name or Wildcat

Stubblefield Canyon Raton - Vermejo Gas

4. Well Location

Unit Letter B 1309' Feet From The North Line and 1533' Feet From The East Line

Section 32 Township 32N Range 20E NMPM Colfax County

10. Date Spudded	11. Date T.D. Reached	12. Date Compl. (Ready to Prod.)	13. Elevations (DF & R(B, RT, GR, etc.)	14. Elev. Casinghead
02/10/01	02/12/01	04/21/01	8174' (GL)	8174'

15. Total Depth	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools	Cable Tools
2545'	2444'		0 - TD		NONE

19. Producing Interval(s) of this completion - Top, Bottom, Name

894' - 2318' Vermejo Coals

20. Was Directional Survey Made

NO

21. Type Electric and Other Logs Run

Sector Bond Log, Array Induction, Compensated Neutron, Litho Density Log

21. Was Well Cored

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	322'	11"	100 sx.	NONE
5 1/2"	15.5	2451'	7 7/8"	350 sx.	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	2383'	No

26. Perforation record (interval, size, and number)

2300'-2301'; 2308'-2310'; 2317'-2318' Shot 4 SPE - 16 holes
2300'-2301'; 2301'-2302'; 2307'-2308'; 2308'-2310'; 2036'-2037'; 2317'-2318' Shot 4 SPE - 14 holes
Vermejo Coals
2185'-2187'; 2218'-2226' Shot 4 SPE - 40 holes
2082'-2086'; 2095'-2097'; 2105'-2107'; 2137'-2139' Shot 4 SPE - 40 holes
1312'-1314'; 1352'-1354' Shot 4 SPE - 16 holes
894'-897'; 930'-932' Shot 4 SPE - 20 holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
894' - 2318'	68,700 lbs 20/40 mesh sand
	141,000 lbs 12/20 mesh sand

28. PRODUCTION

Date First Production

01-29-01

Production Method (Flowing, gas lift, pumping - Size and type pump)
Pumping water up 2 7/8" tubing w/ 095 PC Pump. Flowing gas up 5 1/2" casing

Well Status (Prod. or Shut-in)
Prod.

Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl	Gas - Oil Ratio
01-29-01	24 hrs	Full 2		N/A	104	190	N/A
Flow Tubing Press	Casing Pressure 150 psi	Calculated 24-Hour Rate	Oil - Bbl N/A	Gas - MCF 104	Water - Bbl 190	Oil Gravity - API - (corr.) N/A	

29. Disposition of Gas (Solid use, for fuel, vented, etc.)

Sold, used for fuel.

Test Witnessed By:

Mike Potter

30. Test Attachments

I, William Ordemann, hereby certify that the information shown on each page of this form is true and complete to the best of my knowledge and belief.

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anyh	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Ortiz
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. Raton-surface to
T. Blinbry	T. Gr. Wash	T. Morrison	T. Vermajo 2,070'
T. Tubb	T. Delaware Sand	T. Todillo	Trinidad 2,325'
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1. from.....to.....	No. 3. from.....to.....
No. 2. from.....to.....	No. 4. from.....to.....
Include data on rate of water inflow and elevation to which water rose in hole.	
No. 1, from.....to.....	No. 2, from.....to.....
No. 3, from.....to.....	No. 4, from.....to.....

LITHOLOGY RECORD

From	To	Thickness In Feet	Lithology
------	----	----------------------	-----------

(Attach additional sheet if necessary)