Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office Revised March 25, 1999 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 30-007-20228 District II OIL CONSERVATION DIVISION 811 South First, Artesia, NM 87210 5. Indicate Type of Lease 2040 South Pacheco District III STATE FEE 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV State Oil & Gas Lease No. 2040 South Pacheco, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH VPR D PROPOSALS.) 1 Type of Well: Oil Well Gas Well Other X Coalbed Methane Name of Operator 8. Well No. 56 EL PASO ENERGY RATON, L.L.C. 3 Address of Operator 9. Pool name or Wildcat P.O. Box 190, Raton, NM Well Location 4 Unit Letter M: 760' feet from the South line and 1299' feet from the West Section Township 31N Range 18E NMPM COLFAX County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8358' (GL) 11. Check Appropriate Box to Indicate Nature of Notice. Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND **ABANDONMENT** PULL OR ALTER CASING **MULTIPLE** CASING TEST AND COMPLETION **CEMENT JOB** OTHER: OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 02/22/01: Spud @ 2:15 AM, 02/22/01. Drill 11" surface hole to 330'. Run 14 its. of 8-5/8" 23 ppf to 319'. Halliburton mixed and pumped 100 sx 14 lb/gal 02/23/01: Midcon II PP with 6% salt, 5#/sx gilsonite & 0.3% versaset. Circulate 5 bbls cement to surface. WOC 8 hrs. Test surface csg to 500 psi for 30 minutes. Drill 7 7/8" hole from 335'-360'. Drill 7 7/8" hole from 535'-1710'. RU Schlumberger & log. MIRU Leed. Run 40 jts. of 5 ½", 15.5 ppf to 1652'. 02/24/01: MIRU Halliburton. Mix and pump 10 bbl gelled water with 5 lb/bbl BaraCarb, 5 lb/bbl Magma Fiber followed by 02/25/01: 265 sx 13 lb/gal Midcon II PP, 6% salt, 2 lb/sx Granulite TR ¼, 5 lb/sx Gilsonite, 0.3% Versaset & 0.3% Super CBL. Plug down @ 10:30 AM 02/25/01 with 1375 psi. Circulated 21 bbls cement to surface. I hereby certify that the information above is true and complete to the best of my knowledge and belief. Wellen M Chilenn TITLE Engineer SIGNATURE DATE 04/05/01 Telephone No. (505) 445-6724 William M. Ordemann Type or print name (This space for State use) THE DISTRICT SUPERVISOR DATE 4/5/2001 APPPROVED BY

Conditions of approval, if an