Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office Energy, Minerals and Natural Resources Revised March 25, 1999 District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 30-007-20232 District II OIL CONSERVATION DIVISION 811 South First, Artesia, NM 87210 5. Indicate Type of Lease District III 2040 South Pacheco STATE **FEE** 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 District IV State Oil & Gas Lease No. 2040 South Pacheco. Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH VPR D PROPOSALS.) 1. Type of Well: Oil Well Other X Coalbed Methane Gas Well Name of Operator 8. Well No. 65 EL PASO ENERGY RATON, L.L.C. 9. Pool name or Wildcat 3. Address of Operator P.O. Box 190, Raton, NM 87740 Well Location N: 461' feet from the South line and 1435' feet from the West Unit Letter line Section Township 31N Range 18E NMPM COLFAX County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8749' (GL) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND **TEMPORARILY ABANDON ABANDONMENT** PULL OR ALTER CASING MULTIPLE CASING TEST AND COMPLETION **CEMENT JOB** OTHER: OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 02/17/01: Spud @ 8:00 AM, 02/16/01. Drill 11" surface hole to 325'. Run 14 jts. of 8-5/8" 23 ppf to 316'. Halliburton mixed and pumped 100 sx 14 lb/gal Midcon II PP with 6% salt, 5#/sx gilsonite & 0.3% versaset. Circulate 7 bbls cement to surface. WOC 8 hrs. Test surface csg to 500 psi for 30 minutes. Drill 7 7/8" hole from 325'-700'. Drill 7 7/8" hole from 700'-2192'. RU Schlumberger & log. MIRU Leed. Run 49 jts. of 5 ½", 15.5 ppf to 2017'. 02/18/01: 02/19/01: MIRU Hall burton. Mix and pump 10 bbl gelled water with 5 lb/bbl BaraCarb, 5 lb/bbl Magma Fiber followed by 330 sx 13 lb/gal Midcon II PP, 6% salt, 2 lb/sx Granulite TR ¼, 5 lb/sx Gilsonite, 0.3% Versaset & 0.3% Super CBL. Plug down @ 5:46 AM 02/18/01 with 1500 psi. Circulated 20 bbls cement to surface. I hereby certify that the information above is true and complete to the best of my knowledge and belief. **SIGNATURE** Men TITLE Engineer DATE 03/21/01 William M. Ordemann Telephone No. (505) 445-6724 Type or print name

(This space for State use)

APPPROVED BY Conditions of approval, if an TITLE DISTRICT SUPERVISOR DATE 3/23/0/