

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies

State of New Mexico
Energy, Minerals and Natural Resources

Form C-105
Revised March 25, 1999

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Artec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20247

5. Indicate Type of Lease

STATE FEE X

State Oil & Gas Lease No. ■

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER X COALBED METHANE
b. Type of Completion:
NEW WORK PLUG DIFF. RESVR. OTHER
WELL ☒ OVER ☐ DEEPEN ☐ BACK ☐

7. Lease Name or Unit Agreement Name

VPR E

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

8. Well No.

03

3. Address of Operator

PO BOX 190
RATON, NEW MEXICO 87740

9. Pool name or Wildcat

Stubblefield Canyon Raton - Vermejo Gas

4. Well Location

Unit Letter O : 920 Feet From The South Line and 1474 Feet From The East Line

Section 06 Township 31N Range 19E NMPM COLFAX County

10. Date Spudded

03/30/01

11. Date T.D. Reached

03/31/01

12. Date Compl. (Ready to Prod.)

06/13/01

13. Elevations (DF& R(B. RT, GR, etc.)

8268'

14. Elev. Casinghead

8268'

15. Total Depth

1861'

16. Plug Back T.D.

1777'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools
0 - TD

Cable Tools
None

19. Producing Interval(s), of this completion - Top. Bottom, Name

966' - 1616'

VERMEJO COALS

20. Was Directional Survey Made
No

21. Type Electric and Other Logs Run

Array Induction, Compensated Density, and Cement Bond Log.

21. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24 lb.	323'	11"	100 sx.	None
5 1/2"	15.5 lb.	1797'	7 7/8"	272 sx.	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	1684'	N/A

26. Perforations

1591' - 1594', 1602' - 1604', 1612' - 1616' Shot 4 SPF, 36 Holes
966' - 968', 985' - 987', 1032' - 1034' Shot 4 SPF, 24 Holes

Vermejo Coals

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
966' - 1616'	101,200 lbs 16/30 mesh sand

28. PRODUCTION

Date First Production 06/15/01	Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/095 pc pump. Flowing gas up 5 1/2" casing.				Well Status (Prod. or Shut-in) Prod.		
Date of Test 06/15/01	Hours Tested 24 Hours	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 22	Water - Bbl 367	Gas - Oil Ratio N/A
Flow Tubing Press.	Casing Pressure 15 psi	Calculated 24- Hour Rate	Oil - Bbl N/A	Gas - MCF 22	Water - Bbl 367	Oil Gravity - API - (Corr.) N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel

Test Witnessed By:

Mike Potter

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature:

William M. Ordemann

Printed

Name:

William M. Ordemann

Title: Engineer

Date: 08/01/01

