

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO. 30-007-20281

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR D

8. Well No. 80

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190 RATON, NM 87740

4. Well Location

Unit Letter F : 2179.0 feet from the North line and 1505.0 feet from the West line

Section 15 Township 30N Range 18E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
8321' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐ COMPLETION ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

02/09/02 Halliburton ran Cement Bond Log. TOC at surface.

03/20/02 Halliburton perf'd 1<sup>st</sup> stage: 2205'-2210', 2218'-2221' 4 SPF 32 Holes  
Halliburton frac'd 1<sup>st</sup> stage: Pumped 9.5 BBLS HCL acid, 429,356 (scf) nitrogen foam with 56,320 lbs of 16/30 mesh sand at 20.0 bpm.  
Halliburton perf'd 2<sup>nd</sup> stage: 2131'-2133', 2136'-2138' 4 SPF 16 Holes  
Halliburton frac'd 2<sup>nd</sup> stage: Pumped 4.8 bbls HCL acid, 246,748 (scf) nitrogen foam with 25,420 lbs of 16/30 mesh sand at 20.6 bpm.  
Halliburton perf'd 3<sup>rd</sup> stage: 1959'-1961', 1964'-1968' 4 SPF 24 Holes  
Halliburton frac'd 3<sup>rd</sup> stage: Pumped 7.1 bbls HCL acid, 257,126 (scf) nitrogen foam with 33,530 lbs of 16/30 mesh sand at 20.7 bpm.  
Halliburton perf'd 4<sup>th</sup> stage: 1665'-1667', 1670'-1672' 4 SPF 16 Holes  
Halliburton frac'd 4<sup>th</sup> stage: Pumped 4.8 bbls HCL acid, 182,657 (scf) nitrogen foam with 4,710 lbs of 16/30 mesh sand at 12.4 bpm.  
Halliburton perf'd 5<sup>th</sup> stage: 1603'-1605' 4 SPF 8 Holes  
Halliburton frac'd 5<sup>th</sup> stage: Pumped 2.4 bbls HCL acid, 190,625 (scf) nitrogen foam with 190,625 lbs of 16/30 mesh sand at 12.5 bpm  
Halliburton perf'd 6<sup>th</sup> stage: 1513'-1515' 4 SPF 8 Holes  
Halliburton frac'd 6<sup>th</sup> stage: Pumped 2.4 bbls HCL acid, 197,947 (scf) nitrogen foam with 1,550 lbs of 16/30 mesh sand at 12.4 bpm  
Halliburton perf'd 7<sup>th</sup> stage: 1001'-1004' 4 SPF 12 Holes  
Halliburton frac'd 7<sup>th</sup> stage: Pumped 4 bbls HCL acid, 220,300 (scf) nitrogen foam with 16,260 lbs of 16/30 mesh sand at 12.5 bpm  
03/28/02 Installed rods, tubing, and pump. Well is ready to be put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 05/14/02  
Type or print name: Shirley A. Mitchell Telephone No.: (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 5/21/02  
Conditions of approval, if any: