Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office Energy, Minerals and Natural Resources District I Revised March 25, 1999 1625 N. French Dr., Hobbs, NM 87240 WELL API NO. District II 30-007-20299 OIL CONSERVATION DIVISION 811 South First, Artesia, NM 87210 5. Indicate Type of Lease District III 2040 South Pacheco 1000 Rio Brazos Rd., Aztec, NM 87410 STATE \square **FEE** Santa Fe, NM 87505 **District IV** 6. State Oil & Gas Lease No. 2040 South Pacheco, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) VPR D 1. Type of Well: Oil Well Gas Well Other COALBED METHANE Name of Operator 8. Well No. 86 EL PASO ENERGY RATON, L.L.C. Address of Operator 9. Pool name or Wildcat P.O. BOX 190 **RATON, NM 87740** Well Location Unit Letter L: 1508.6 feet from the South line and 1113.4 feet from the West line Section 3 Township 30N Range 18E NMPM COLFAX County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8113' (GR) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON** CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND **ABANDONMENT PULL OR ALTER CASING MULTIPLE** CASING TEST AND COMPLETION **CEMENT JOB** OTHER: OTHER: COMPLETION 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 02/09/02 Halliburton ran Cement Bond Log. TOC at surface. 04/22/02 Halliburton perf'd 1st stage: 1256' - 1258' 3 SPF 5 Holes Halliburton frac'd 1st stage: Pumped 2.4 bbls HCL acid with 184,000 lbs of 16/30 Mesh Sand at 10.1 bpm, ATP at 1610 psi. 04/23/02 Halliburton perf'd 2nd stage: 1191'-1193', 1204'-1206' 3 SPF 10 Holes Halliburton frac'd 2nd stage: Pumped 3.6 bbls HCL acid with 28,453 lbs of 16/30 Mesh Sand at 16 bpm, ATP at 1762 psi. Halliburton perf'd 3rd stage: 1078'- 1080', 1122'- 1124', 1138'- 1140' 3 SPF 15 Holes Halliburton frac'd 3rd stage: Pumped 6 bbls HCL acid with 49,902 lbs of 16/30 Mesh Sand at 16 bpm, ATP at 1792 psi. Halliburton perf'd 4th stage: 999'- 1004', 1016'- 1018' 3 SPF 19 Holes Halliburton frac'd 4th stage: Pumped 8.3 bbls of HCL acid with 66,144 lbs of 16/30 Mesh Sand at 16.3 bpm, ATP at 1348 psi. 05/10/02 Installed rods, tubing, and pump. Well is ready to be put on production. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE Shirlant. mithell TITLE Field Adm Specialist ____DATE ____ Type or print name: Shirley A. Mitchell Telephone No.: (505) 445-6785 (This space for State use) TITLE DISTRICT SUPERVISOR DATE 6/7/02 APPPROVED BY Conditions of approval, if any