

Submit To Appropriate District Office

State Lease - 6 copies

Fee Lease - 5 copies

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Frances
Santa Fe, NM 87505

Form C-105

Revised March 25, 1999

WELL API NO. 30-007-20315

5. Indicate Type of Lease

STATE FEE X

State Oil & Gas Lease No. ■

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER X COALBED METHANE

b. Type of Completion:

NEW WORK PLUG DIFF.
WELL. ☒ OVER ☐ DEEPEN ☐ BACK ☐ RESVR ☐ OTHER

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

PO BOX 190
RATON, NEW MEXICO 87740

4. Well Location

Unit Letter O 1299.6 Feet From The South Line and 2004.1 Feet From The East Line

Section 8 Township 31N Range 19E NMPM COLFAX County

10. Date Spudded

02/07/02

11. Date T.D. Reached

02/08/02

12. Date Compl. (Ready to Prod.)

05/22/02

13. Elevations (DF & R(B, RT, GR, etc.)

7957'

14. Elev. Casinghead

7957'

15. Total Depth

2000'

16. Plug Back T.D.

1967'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools
0 - TDCable Tools
None

19. Producing Interval(s), of this completion - Top, Bottom, Name

1204' - 1677' VERMEJO COALS

20. Was Directional Survey Made
No

21. Type Electric and Other Logs Run

Mud Log, Array Induction, Compensated Density, and Cement Bond Log.

21. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24 lb.	323'	11"	85 sx.	None
5 1/2"	15.5 lb.	1983'	7 7/8"	301 sx.	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	1870'	N/A

26. Perforations

1665' - 1667' 1675' - 1677' 3 SPF 10 Holes
1524' - 1526' 3 SPF 5 Holes
1501' - 1505' 3 SPF 5 Holes
1471' - 1473' 3 SPF 5 Holes
1278' - 1280' 3 SPF 5 Holes
1204' - 1206' 3 SPF 5 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED
1204' - 1677' 88.510 16/30 mesh sand

28. PRODUCTION

Date First Production 06/04/02		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/ 30-11-95 pc pump. Flowing gas up 5 1/2" casing.			Well Status (Prod. or Shut-in) Prod.		
Date of Test 06/04/02	Hours Tested 24 Hours	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 69	Water - Bbl. 0	Gas - Oil Ratio N/A
Flow Tubing Press.	Casing Pressure 510 psi	Calculated 24- Hour Rate	Oil - Bbl N/A	Gas - MCF 69	Water - Bbl. 0	Oil Gravity - API - (Corr.) N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel

Test Witnessed By:

Gary Blundell

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature: Shirley Mitchell

Printed

Name: Shirley A. Mitchell

Title: Field Adm. Specialist Date: 07/31/02

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinebry	T. Gr. Wash
T. Tubb	T. Delaware Sand
T. Drinkard	T. Bone Springs
T. Abo	T.
T. Wolfcamp	T.
T. Penn	T.
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otztze
Base Greenhorn	T. Granite
T. Dakota	T. Raton – Surface
T. Morrison	T. Vermejo
T. Todilto	T. Trinidad
T. Entrada	
T. Wingate	
T. Chinle	
T. Permian	
T. Penn "A"	

OIL OR GAS SANDS
OR ZONES

No. 1, from.....to.....

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology