

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. <b>30-007-20336</b>
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other X Coalbed Methane		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator <b>EL PASO ENERGY RATON, L.L.C.</b>		6. State Oil & Gas Lease No.
3. Address of Operator <b>P.O. Box 190, Raton, NM 87740</b>		7. Lease Name or Unit Agreement Name: <b>VPR A</b>
4. Well Location  Unit Letter <u>E</u> : <u>1863.0</u> feet from the <u>North</u> line and <u>1068.2</u> feet from the <u>West</u> line  Section <u>12</u> Township <u>31N</u> Range <u>19E</u> NMPM COLFAX County		8. Well No. <b>80</b>
10. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>8292' (GL)</b>		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/16/02 Spud in @ 11:00 p.m. Drill 11" surface hole to 330'. Ran 10 jts of 8 5/8", J-55, 23 ppf ST&C casing to 326'. Halliburton mixed and pumped 85 sks Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 30 psi with 6% salt, 5#/sx gilsonite, .3% versaset. Circulated 2 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 min.

03/17/02 Drill 7 7/8" hole f/ 330' - 2635'. Reached TD 2635' at 4:40 a.m. MIRU Schlumberger & log well. Ran 60 jts of 5 1/2", M-50, 15.5 ppf LT & C casing to 2554'. Halliburton mixed and pump 20 bbls gel pre flush at 4 bpm at 55 psi, 357 sks Midcon II, 13.0 ppg, yield 2.04, with 6% salt, .3% versaset, 5#/sx gilsonite, and .3% Super CBL. Plug down @ 3:42 a.m. with 1600 psi. Circulated 11 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE Engineer DATE 03/26/02

Type or print name Donald R. Lankford Telephone No. (505) 445-6721

(This space for State use)

APPROVED BY R. E. Johnson TITLE DISTRICT SUPERVISOR DATE 3/28/02

Conditions of approval, if any: