

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-007-20352

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR A

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐

Gas Well ☒

Other ☒ Coalbed Methane

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. Box 190, Raton, NM 87740

4. Well Location

Unit Letter B : 323.3 feet from the North line and 1682.2 feet from the East line

Section 36 Township 32N Range 19E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

8137' (GL)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/23/02 Spud in @ 6:00 a.m. Drill 11" surface hole to 330'. Ran 10 jts of 8 5/8", J-55, 23 ppf ST&C casing to 326'. Halliburton mixed and pumped 85 sks Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 85 psi with 6% salt, 5#/sx gilsonite, .3% versaset. Circulated 1 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 min.

03/24/02 Drill 7 7/8" hole @ 330' - 2575'. Reached TD 2575' at 9:30 a.m. MIRU Schlumberger & log well. Ran 63 jts of 5 1/2", M-50, 15.5 ppf LT & C casing to 2511'. Halliburton mixed and pump 20 bbls gel pre flush at 3 bpm at 60 psi, 333 sks Midcon II, 13.0 ppg, yield 2.04, with 6% salt, .3% versaset, 5#/sx gilsonite, and .3% Super CBL. Plug down @ 6:43 p.m. with 1200 psi. No cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 03/28/02

Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY R. E. Johnson TITLE **DISTRICT SUPERVISOR** DATE 4/5/02

Conditions of approval, if any: