

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St Frances
Santa Fe, NM 87505

WELL API NO. 30-007-20365
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: VPR A
8. Well No. 102
9. Pool name or Wildcat
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 7784' (GL)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other ☒ Coalbed Methane

2. Name of Operator
EL PASO ENERGY RATON, L.L.C.

3. Address of Operator
P.O. Box 190, Raton, NM 87740

4. Well Location
Unit Letter **A** : **795** feet from the **North** line and **236** feet from the **East** line
Section **31** Township **32N** Range **21E** NMPM **Colfax** County

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01/26/03 Spud in @ 6:00 p.m. Drill 11" surface hole to 340'. Ran 10 jts of 8 5/8", J-55, 24 ppf ST&C casing to 331'. Halliburton mixed and pumped 150 sks Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 85 psi with 6% salt, .3% gilsonite, .3% versaset, and 25# flocele per sack. Circulated 17 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 min.

01/27/03 Drill 7 7/8" hole f/ 340' - 2155'. Reached TD 2155'. MIRU Schlumberger & log well. Ran 12 jts of 5 1/2", J-55, and 50 jts of 5 1/2", M-50, 15.5 ppf LT & C casing to 2125'. Halliburton mixed and pump 20 bbls gel pre flush at 3 bpm at 30 psi, 295 sks Midcon II, 13.0 ppg, yield 2.04, .3% versaset, .5#/sk gilsonite, 2#/sk granulate, 6% salt and .1% Super CBL. Plug down @ 3:43 a.m. Circulated 25 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 01/30/03

Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 2/5/03
Conditions of approval, if any: