

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO. 30-007-20371

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR C

8. Well No. 97

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190 RATON, NM 87740

4. Well Location

Unit Letter B : 1225 feet from the North line and 1995 feet from the East line
Section 30 Township 32N Range 21E NMPM Colfax County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

7635' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: COMPLETION ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02-07-03 HES ran cement bond log. TOC at 56'.

04-02-03 HES perf'd 1st stage: 1803' - 1805'; 1810' - 1812' 3 SPF 10 Holes (7' of coal)

HES frac'd 1st stage: Fracture treatment and 70,720 lbs of 20/40 Ottawa Sand, average pressure at 4,090 psi, Final ISIP at 2,870 psi.

HES perf'd 2nd stage: 1652' - 1654' 3 SPF 5 Holes (2' of coal)

HES frac'd 2nd stage: Fracture treatment and 20,870 lbs of 20/40 Ottawa Sand, average pressure at 3,922 psi, Final ISIP at 2,504 psi.

HES perf'd 3rd stage: 1446' - 1448' 3 SPF 5 Holes (1' of coal)

HES frac'd 3rd stage: Fracture treatment and 10,730 lbs of 20/40 Ottawa Sand, average pressure at 3,577 psi, Final ISIP at 2,237 psi.

HES perf'd 4th stage: 1023' - 1025' 3 SPF 5 Holes (2' of coal)

HES frac'd 4th stage: Fracture treatment and 20,520 lbs of 20/40 Ottawa Sand, average pressure at 2,952 psi, Final ISIP at 785 psi.

HES perf'd 5th stage: 944' - 946' 3 SPF 5 Holes (2' of coal)

HES frac'd 5th stage: Fracture treatment and 22,000 lbs of 20/40 Ottawa Sand, average pressure at 2,941 psi, Final ISIP at 928 psi.

04-04-03 Air clean out, installed rods, tubing, and pump. Well is ready to be tested and put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 04/30/03
Type or print name: Shirley A. Mitchell Telephone No.: (505) 445-6785

(This space for State use)
APPROVED BY [Signature] TITLE _____ DATE 5/5/03
Conditions of approval, if any: _____