

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO. 30-007-20373
5. Indicate Type of Lease STATE ☐ FEE ☒
State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER _____	7. Lease Name or Unit Agreement Name VPR A
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER _____	8. Well No. 108
2. Name of Operator EL PASO ENERGY RATON, L.L.C.	9. Pool name or Wildcat Stubblefield Canyon Raton - Vermejo Gas
3. Address of Operator P.O. BOX 190, RATON, NEW MEXICO 87740	

4. Well Location Unit Letter G : 1691 Feet From The North Line and 1967 Feet From The East Line							
Section	29	Township	32N	Range	21E	NMPM	Colfax County
10. Date Spudded	11. Date T.D. Reached	12. Date Compl. (Ready to Prod.)	13. Elevations (DF& R(B. RT, GR. etc.)		14. Elev. Casinghead		
01/12/03	01/13/03	03/11/03	7369' (GL)		7369'		
15. Total Depth	16. Plug Back T.D.	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools	Cable Tools		
1765'	1700'			0 - TD	NONE		
19. Producing Interval(s), of this completion - Top, Bottom, Name 1357' - 1508' Vermejo - Raton Coals					20. Was Directional Survey Made NO		
21. Type Electric and Other Logs Run Mud Log, Epithermal Neutron Litho Density, Array Induction Linear Correlation, and Acoustic Cement Bond Log					22. Was Well Cored No		

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	322'	11"	100 sx	None
5 1/2"	15.5	1741'	7 7/8"	239 sx	
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
25. TUBING RECORD					
SIZE	DEPTH SET	PACKER SET			
2 7/8"	1558'	No			
26. Perforation record (interval, size, and number)					
1504' - 1508', 1518' - 1520' 3 SPF 16 Holes 1468' - 1470' 3 SPF 5 Holes 1382' - 1385' 3 SPF 11 Holes 1357' - 1359' 3 SPF 5 Holes					
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
DEPTH INTERVAL			AMOUNT AND KIND MATERIAL USED		
1357' - 1520'			163,850 lbs 20/40 Ottawa Sand		

28. PRODUCTION							
Date First Production 03/15/03		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/30-N-95 PC Pump. Flowing gas up 5 1/2" Casing.				Well Status (Prod. or Shut-in) Prod.	
Date of Test 03/15/03	Hours Tested 24 hrs.	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 0	Water - Bbl 156	Gas - Oil Ratio N/A
Flow Tubing Press.	Casing Pressure 0	Calculated 24-Hour Rate	Oil - Bbl N/A	Gas - MCF 0	Water - Bbl 156	Oil Gravity - API - (Corr.) N/A	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.						Test Witnessed By: Jerry Colburn	

30. List Attachments			
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.			
Signature: <i>Shirley A. Mitchell</i>	Printed Shirley A. Mitchell	Title Field Adm Specialist	Date: 03/25/03

