

RECEIVED

Form C-103
Supersedes Old
C-102 and C-103
EFFECTIVE 1-1-71
CONSERVATION COMM.

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	✓
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 1-26046
7. Unit Agreement Name
8. Farm or Lease Name Hatch PP
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Hudon

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Continental Oil Company
3. Address of Operator Box 460, Hobbs, New Mexico
4. Location of Well UNIT LETTER <u>F</u> <u>2080</u> FEET FROM THE <u>North</u> LINE AND <u>1780</u> FEET FROM THE <u>West</u> LINE, SECTION <u>27</u> TOWNSHIP <u>6N</u> RANGE <u>24E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 9 7/8" hole on 12-6-71. Set 7 5/8" casing at 323'. Cemented w/ 150 sacks class 'C' cement w/ 4% gel, 2% CaCl and 1/4# floccle per sack. Cement circulated. WOC 24 hours. Tested casing w/ 1000 psi for 30 minutes. Held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Administrative Supervisor</u>	DATE <u>12-7-71</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>Oil & Gas Inspector</u>	DATE <u>2/8/72</u>
CONDITIONS OF APPROVAL, IF ANY:		