

(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(Other instructions on reverse side)

RECEIVED

LEASE DESIGNATION AND SERIAL NO.

EAP 13340

6. INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

JAN 10 1972

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

CONSERVATION

COMM.

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER

Dry hole

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)
At surface

U. S. GEOLOGICAL SURVEY

990' FSL and 1980' FEL of sec 13

8. FARM OR LEASE NAME

Williams Federal A

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA

Sec 13 T-5N R-23E

14. PERMIT NO.

16. ELEVATIONS (Show whether DF, RT, GR, etc.)

4386.7' gr

Guadalupe N. Mex

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

T.D. 1285'. This well was plugged and abandoned by setting cement plugs as follows: 50 sacks from 1280' to 1080' across Morieta, 50 sacks from 810' to 610' across San Andres, 50 sacks from 540' to 320' across surface of csg shoe and 10 sacks from 40' to surface. Installed dry hole marker. Restored location for inspection. Well plugged and abandoned as of 12-31-71.

Note: Verbal approval to perform this work was obtained from your office.

18. I hereby certify that the foregoing is true and correct

SIGNED

Hugh Drake

TITLE

Administrative Supervisor

DATE

1-4-72

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

USGS TST Durango, Colo File

*See Instructions on Reverse Side