

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Petroleum Development Corporation		8. Farm or Lease Name Vaughn State
3. Address of Operator 9720-B Candelaria N.E., Albuquerque, N.M. 87112		9. Well No. 1
4. Location of Well UNIT LETTER <u>E</u> <u>682</u> FEET FROM THE <u>West</u> <u>2006</u> FEET FROM THE <u>North</u> <u>16</u> LINE, SECTION <u>6N</u> TOWNSHIP <u>17E</u> RANGE <u>17E</u> N.M.P.M.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether Dr RT, GR, etc.) 5744 GL		12. County Guadalupe

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 11 a.m. 6/9/74. Ran 5 jts. (217.67) 10-3/4", 40.48 new casing. Set at 232'. Cemented with 150 sacks, Class "C", 2% CaCl + 1/4 Flocele/sack by Howco. P.D. @ 7:00 p.m. 6/11/74. Circulated 20 sacks cement. WOC 12 hours. Tested BOP and casing to 500 psi for 10 minutes before drilling out.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christena Marsland TITLE Secretary DATE 6/14/74

APPROVED BY Carl Ulvog TITLE Secretary DATE 6/21/74

CONDITIONS OF APPROVAL, IF ANY: