

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L 6331

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Public Lands Exploration Co., Inc.	8. Farm or Lease Name State
3. Address of Operator P. O. Box 29119, Dallas, Texas 75229	9. Well No. 2
4. Location of Well UNIT LETTER B . 500 FEET FROM THE North LINE AND 1650 FEET FROM THE East LINE, SECTION 15 TOWNSHIP 11N RANGE 25E NMPM.	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4550.7' GL	12. County Guadalupe

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 11" hole at 2:00 PM 3-1-80. TD 30'. Ran 30' of 8 5/8" 32# casing and cemented from TD to surface with 12 sacks of neat cement containing 2% calcium chloride. Drilled 6 3/4" hole to 473' TD. Ran 472.50' of 4 1/2" 10.5# K-55 casing. Installed 6 3/4" bit on bottom of casing. Cemented casing as follows: Pumped 20 bbls. of gelled 2% KCl water, 45 sacks of class "H" cement containing 0.6% Halad 9 and 45 sacks of class "H" cement with 2% calcium chloride. Cement circulated within 70' from surface. Pumped 20 sacks of class "H" cement with 2% calcium chloride down outside of casing and brought cement back to surface. Pressure tested casing to 600 psig for 30 minutes. Casing held OK.

RECEIVED
MAY 23 1980
SANTA FE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles C. Joy TITLE Agent DATE May 15, 1980

APPROVED BY Carl Ullery TITLE Geologist DATE 5/23/80

CONDITIONS OF APPROVAL, IF ANY